

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P1500394

Luminaire Tested: LD4C25D010 EU4259040 4LBMH

Issue Date: 2/8/2022

Test Information

Test Method: LM-79-2019
Report Number: P1500394
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4C25D010 EU4259040 4LBMH
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS AND 4LBM TRIM FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1911.0 lumens
Efficiency: N/A
Efficacy: 60.7 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1500394

CATALOG NUMBER: LD4C25D010 EU4259040 4LBMH

Luminous Intensity Polar Plot



TEST NUMBER: P1500394

CATALOG NUMBER: LD4C25D010 EU4259040 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	232795
5°	229417
10°	219820
15°	207621
20°	193806
25°	175935
30°	146881
35°	106408
40°	66619
45°	38084
50°	19858
55°	11116
60°	7101
65°	4186
70°	3125
75°	1377
80°	2052
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 38084 cd/sqm

TEST NUMBER: P1500394

CATALOG NUMBER: LD4C25D010 EU4259040 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	174.4	9.1
10°-20°	457.4	23.9
20°-30°	587.9	30.8
30°-40°	442.3	23.1
40°-50°	177.6	9.3
50°-60°	50.5	2.6
60°-70°	16.0	0.8
70°-80°	4.6	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1219.6	63.8
0°-40°	1661.9	87.0
0°-60°	1890.0	98.9
0°-90°	1911.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1911.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1895	
5°	1860	174
15°	1632	457
25°	1298	588
35°	710	442
45°	219	178
55°	52	50
65°	14	16
75°	3	5
85°	0	0
90°	0	

TEST NUMBER: P1500394

CATALOG NUMBER: LD4C25D010 EU4259040 4LBMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1894.9
2.5°	1883.3
5°	1860.3
7.5°	1817.0
10°	1762.1
12.5°	1695.9
15°	1632.4
17.5°	1560.3
20°	1482.4
22.5°	1398.9
25°	1297.9
27.5°	1176.7
30°	1035.4
32.5°	876.7
35°	709.5
37.5°	553.7
40°	415.4
42.5°	305.7
45°	219.2
47.5°	150.0
50°	103.9
52.5°	72.1
55°	51.9
57.5°	37.5
60°	28.9
62.5°	20.2
65°	14.4
67.5°	11.5
70°	8.7
72.5°	5.8
75°	2.9
77.5°	2.9
80°	2.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)