

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P1500420

Luminaire Tested: LD4C50D010 EU4509050 4LBMH

Issue Date: 2/8/2022

Test Information

Test Method: LM-79-2019
Report Number: P1500420
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4C50D010 EU4509050 4LBMH
Description: 4 INCH 5000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND 4LBM TRIM FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4113.0 lumens
Efficiency: N/A
Efficacy: 70.4 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 58.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1500420

CATALOG NUMBER: LD4C50D010 EU4509050 4LBMH

Luminous Intensity Polar Plot



TEST NUMBER: P1500420

CATALOG NUMBER: LD4C50D010 EU4509050 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	501033
5°	493760
10°	473122
15°	446872
20°	417119
25°	378656
30°	316147
35°	229029
40°	143374
45°	81954
50°	42736
55°	23946
60°	15258
65°	9041
70°	6681
75°	2943
80°	4386
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 81954 cd/sqm

TEST NUMBER: P1500420

CATALOG NUMBER: LD4C50D010 EU4509050 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	375.3	9.1
10°-20°	984.5	23.9
20°-30°	1265.2	30.8
30°-40°	951.9	23.1
40°-50°	382.3	9.3
50°-60°	108.7	2.6
60°-70°	34.4	0.8
70°-80°	9.8	0.2
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2625.0	63.8
0°-40°	3576.9	87.0
0°-60°	4068.0	98.9
0°-90°	4113.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4113.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4078	
5°	4004	375
15°	3514	984
25°	2793	1265
35°	1527	952
45°	472	382
55°	112	109
65°	31	34
75°	6	10
85°	0	1
90°	0	

TEST NUMBER: P1500420

CATALOG NUMBER: LD4C50D010 EU4509050 4LBMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	4078.3
2.5°	4053.5
5°	4003.8
7.5°	3910.6
10°	3792.6
12.5°	3650.1
15°	3513.5
17.5°	3358.2
20°	3190.5
22.5°	3010.7
25°	2793.4
27.5°	2532.6
30°	2228.6
32.5°	1887.0
35°	1527.1
37.5°	1191.8
40°	894.0
42.5°	658.0
45°	471.7
47.5°	322.9
50°	223.6
52.5°	155.3
55°	111.8
57.5°	80.7
60°	62.1
62.5°	43.5
65°	31.1
67.5°	24.8
70°	18.6
72.5°	12.4
75°	6.2
77.5°	6.2
80°	6.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)