

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P1500427

Luminaire Tested: LD4C60D010 EU4609030 4LBMH

Issue Date: 2/8/2022

Test Information

Test Method: LM-79-2019
Report Number: P1500427
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4C60D010 EU4609030 4LBMH
Description: 4 INCH 6000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS AND 4LBM TRIM FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4795.9 lumens
Efficiency: N/A
Efficacy: 66.6 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 72
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1500427

CATALOG NUMBER: LD4C60D010 EU4609030 4LBMH

Luminous Intensity Polar Plot



TEST NUMBER: P1500427

CATALOG NUMBER: LD4C60D010 EU4609030 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	584230
5°	575745
10°	551689
15°	521074
20°	486397
25°	441526
30°	368635
35°	267063
40°	167174
45°	95558
50°	49827
55°	27909
60°	17789
65°	10523
70°	7795
75°	3418
80°	5094
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 95558 cd/sqm

TEST NUMBER: P1500427

CATALOG NUMBER: LD4C60D010 EU4609030 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	437.6	9.1
10°-20°	1148.0	23.9
20°-30°	1475.3	30.8
30°-40°	1110.0	23.1
40°-50°	445.8	9.3
50°-60°	126.7	2.6
60°-70°	40.1	0.8
70°-80°	11.4	0.2
80°-90°	1.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3060.9	63.8
0°-40°	4170.9	87.0
0°-60°	4743.4	98.9
0°-90°	4795.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4795.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4756	
5°	4669	438
15°	4097	1148
25°	3257	1475
35°	1781	1110
45°	550	446
55°	130	127
65°	36	40
75°	7	11
85°	0	1
90°	0	

TEST NUMBER: P1500427

CATALOG NUMBER: LD4C60D010 EU4609030 4LBMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	4755.5
2.5°	4726.6
5°	4668.6
7.5°	4560.0
10°	4422.4
12.5°	4256.2
15°	4096.9
17.5°	3915.9
20°	3720.4
22.5°	3510.7
25°	3257.2
27.5°	2953.1
30°	2598.6
32.5°	2200.4
35°	1780.7
37.5°	1389.7
40°	1042.4
42.5°	767.2
45°	550.0
47.5°	376.5
50°	260.7
52.5°	181.0
55°	130.3
57.5°	94.1
60°	72.4
62.5°	50.7
65°	36.2
67.5°	29.0
70°	21.7
72.5°	14.5
75°	7.2
77.5°	7.2
80°	7.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)