

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P1500441

Luminaire Tested: LD4C75D010 EU4759027 4LBMH

Issue Date: 2/8/2022

Test Information

Test Method: LM-79-2019
Report Number: P1500441
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4C75D010 EU4759027 4LBMH
Description: 4 INCH 7500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS AND 4LBM TRIM FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5959.0 lumens
Efficiency: N/A
Efficacy: 73.1 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 81.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1500441

CATALOG NUMBER: LD4C75D010 EU4759027 4LBMH

Luminous Intensity Polar Plot



TEST NUMBER: P1500441

CATALOG NUMBER: LD4C75D010 EU4759027 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	725904
5°	715371
10°	685469
15°	647434
20°	604336
25°	548600
30°	458034
35°	331823
40°	207716
45°	118735
50°	61906
55°	34677
60°	22114
65°	13081
70°	9698
75°	4272
80°	6367
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 118735 cd/sqm

TEST NUMBER: P1500441

CATALOG NUMBER: LD4C75D010 EU4759027 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	543.7	9.1
10°-20°	1426.4	23.9
20°-30°	1833.1	30.8
30°-40°	1379.2	23.1
40°-50°	553.9	9.3
50°-60°	157.5	2.6
60°-70°	49.9	0.8
70°-80°	14.2	0.2
80°-90°	1.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3803.1	63.8
0°-40°	5182.3	87.0
0°-60°	5893.7	98.9
0°-90°	5959.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5959.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5909	
5°	5801	544
15°	5090	1426
25°	4047	1833
35°	2212	1379
45°	683	554
55°	162	157
65°	45	50
75°	9	14
85°	0	1
90°	0	

TEST NUMBER: P1500441

CATALOG NUMBER: LD4C75D010 EU4759027 4LBMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	5908.7
2.5°	5872.7
5°	5800.8
7.5°	5665.8
10°	5494.8
12.5°	5288.3
15°	5090.4
17.5°	4865.4
20°	4622.5
22.5°	4362.0
25°	4047.1
27.5°	3669.2
30°	3228.8
32.5°	2733.9
35°	2212.5
37.5°	1726.6
40°	1295.2
42.5°	953.3
45°	683.4
47.5°	467.9
50°	323.9
52.5°	224.9
55°	161.9
57.5°	117.0
60°	90.0
62.5°	63.0
65°	45.0
67.5°	36.0
70°	27.0
72.5°	18.0
75°	9.0
77.5°	9.0
80°	9.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)