

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P856983

Luminaire Tested: **LX4C15D010 EX4C159040 4LBNH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P856983
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C15D010 EX4C159040 4LBNH
Description: 4 INCH 1500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 4LBN TRIM WITH H FINISH
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 980.0 lumens
Efficiency: N/A
Efficacy: 62.0 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P856983

CATALOG NUMBER: LX4C15D010 EX4C159040 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P856983

CATALOG NUMBER: LX4C15D010 EX4C159040 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	151159
5°	147802
10°	136650
15°	122621
20°	107937
25°	92895
30°	74802
35°	49792
40°	25900
45°	11728
50°	5084
55°	3406
60°	2187
65°	1541
70°	1293
75°	854
80°	0
85°	0



TEST NUMBER: P856983

CATALOG NUMBER: LX4C15D010 EX4C159040 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.0	11.3
10°-20°	269.3	27.5
20°-30°	312.6	31.9
30°-40°	207.0	21.1
40°-50°	58.1	5.9
50°-60°	14.6	1.5
60°-70°	5.5	0.6
70°-80°	1.9	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	692.9	70.7
0°-40°	900.0	91.8
0°-60°	972.6	99.2
0°-90°	980.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	980.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1230	
5°	1198	111
15°	964	269
25°	685	313
35°	332	207
45°	68	58
55°	16	15
65°	5	5
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P856983

CATALOG NUMBER: LX4C15D010 EX4C159040 4LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1230.4
2.5°	1225.1
5°	1198.5
7.5°	1152.3
10°	1095.4
12.5°	1031.5
15°	964.1
17.5°	898.4
20°	825.6
22.5°	758.1
25°	685.3
27.5°	616.1
30°	527.3
32.5°	433.2
35°	332.0
37.5°	237.9
40°	161.5
42.5°	104.7
45°	67.5
47.5°	40.9
50°	26.6
52.5°	19.5
55°	15.9
57.5°	12.5
60°	8.9
62.5°	7.1
65°	5.3
67.5°	3.6
70°	3.6
72.5°	1.8
75°	1.8
77.5°	1.8
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)