

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857082

Luminaire Tested: **LX4C15D010 EX4C159850 4LBWH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857082
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C15D010 EX4C159850 4LBWH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1193.1 lumens
Efficiency: N/A
Efficacy: 75.5 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857082

CATALOG NUMBER: LX4C15D010 EX4C159850 4LBWH

Luminous Intensity Polar Plot





TEST NUMBER: P857082

CATALOG NUMBER: LX4C15D010 EX4C159850 4LBWH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96
2	105	100	95	91	103	98	93	90	95	91	88		91	88	86		89
3	99	91	85	80	97	90	84	80	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	64	74	68	64		72	67	63		70
6	81	71	64	58	80	70	63	58	68	62	58		67	61	57		65
7	76	65	58	53	75	65	58	53	63	57	53		62	56	52		61
8	72	60	53	49	70	60	53	49	59	53	48		58	52	48		57
9	68	56	49	45	66	56	49	45	55	49	44		54	48	44		53
10	64	52	46	41	63	52	46	41	51	45	41		50	45	41		49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	94474
5°	94835
10°	95133
15°	95136
20°	94602
25°	92393
30°	86364
35°	74793
40°	58424
45°	41906
50°	27235
55°	16300
60°	9533
65°	6105
70°	4059
75°	3085
80°	2264
85°	0



TEST NUMBER: P857082

CATALOG NUMBER: LX4C15D010 EX4C159850 4LBWH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.2	6.1
10°-20°	211.0	17.7
20°-30°	311.4	26.1
30°-40°	307.3	25.8
40°-50°	188.1	15.8
50°-60°	72.1	6.0
60°-70°	22.5	1.9
70°-80°	6.6	0.6
80°-90°	0.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	595.7	49.9
0°-40°	903.0	75.7
0°-60°	1163.1	97.5
0°-90°	1193.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1193.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	769	
5°	769	73
15°	748	211
25°	682	311
35°	499	307
45°	241	188
55°	76	72
65°	21	23
75°	6	7
85°	0	1
90°	0	



TEST NUMBER: P857082

CATALOG NUMBER: LX4C15D010 EX4C159850 4LBWH

CANDELA DISTRIBUTION (FULL):

	0°
0°	769.0
2.5°	770.6
5°	769.0
7.5°	767.4
10°	762.6
12.5°	756.1
15°	748.0
17.5°	738.3
20°	723.6
22.5°	707.5
25°	681.6
27.5°	649.2
30°	608.8
32.5°	558.6
35°	498.7
37.5°	432.2
40°	364.3
42.5°	301.1
45°	241.2
47.5°	187.8
50°	142.5
52.5°	105.2
55°	76.1
57.5°	53.4
60°	38.8
62.5°	29.2
65°	21.0
67.5°	16.2
70°	11.3
72.5°	8.1
75°	6.5
77.5°	3.2
80°	3.2
82.5°	1.6
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)