

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857087

Luminaire Tested: **LX4C15D010 EX4C159030 4LBMDLI**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P857087
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-8)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C15D010 EX4C159030 4LBMDLI
Description: 4 INCH 1500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LRMD45 TRIM WITH LI FINISH, DIM TO WARM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1480.0 lumens
Efficiency: N/A
Efficacy: 63.2 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.82
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 23.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857087

CATALOG NUMBER: LX4C15D010 EX4C159030 4LBMDLI

Luminous Intensity Polar Plot





TEST NUMBER: P857087

CATALOG NUMBER: LX4C15D010 EX4C159030 4LBMDLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	63		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		67
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		63

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	238827
5°	246966
10°	249472
15°	224727
20°	186759
25°	146520
30°	107231
35°	55416
40°	26317
45°	9243
50°	2083
55°	1371
60°	934
65°	698
70°	503
75°	332
80°	212
85°	0



TEST NUMBER: P857087

CATALOG NUMBER: LX4C15D010 EX4C159030 4LBMDLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	191.3	12.9
10°-20°	486.7	32.9
20°-30°	492.5	33.3
30°-40°	251.1	17.0
40°-50°	49.2	3.3
50°-60°	6.0	0.4
60°-70°	2.4	0.2
70°-80°	0.9	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1170.4	79.1
0°-40°	1421.5	96.0
0°-60°	1476.6	99.8
0°-90°	1480.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1480.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1944	
5°	2003	191
15°	1767	487
25°	1081	492
35°	370	251
45°	53	49
55°	6	6
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P857087

CATALOG NUMBER: LX4C15D010 EX4C159030 4LBMDLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1944.0
2.5°	1962.0
5°	2002.6
7.5°	2025.9
10°	1999.8
12.5°	1911.9
15°	1766.9
17.5°	1595.8
20°	1428.5
22.5°	1255.2
25°	1080.9
27.5°	907.2
30°	755.9
32.5°	569.6
35°	369.5
37.5°	247.4
40°	164.1
42.5°	103.0
45°	53.2
47.5°	19.0
50°	10.9
52.5°	8.1
55°	6.4
57.5°	5.0
60°	3.8
62.5°	3.1
65°	2.4
67.5°	1.7
70°	1.4
72.5°	1.0
75°	0.7
77.5°	0.7
80°	0.3
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)