

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857598

Luminaire Tested: **LX4C30D010 EX4C309050 4LBMDLI**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P857598
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-8)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309050 4LBMDLI
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 4LRMD45 TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2516.0 lumens
Efficiency: N/A
Efficacy: 79.6 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.82
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857598

CATALOG NUMBER: LX4C30D010 EX4C309050 4LBMDLI

Luminous Intensity Polar Plot





TEST NUMBER: P857598

CATALOG NUMBER: LX4C30D010 EX4C309050 4LBMDLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	109	107		111	109	107	105		105	103	102		101	100	99		98	97	96
2	109	104	100	97		107	102	99	96		99	96	94		96	94	92		94	92	90
3	104	98	93	89		102	96	92	89		94	90	87		91	88	86		89	87	85
4	99	92	87	83		97	91	86	82		89	85	81		87	83	80		85	82	79
5	94	87	81	77		93	86	81	77		84	79	76		82	78	75		81	77	75
6	90	82	76	72		89	81	76	72		80	75	71		78	74	71		77	73	70
7	86	77	72	68		85	77	71	68		75	71	67		74	70	67		73	69	67
8	82	73	68	64		81	73	67	64		72	67	63		71	66	63		70	66	63
9	79	70	64	60		78	69	64	60		68	63	60		67	63	60		66	63	60
10	75	66	61	57		74	66	61	57		65	60	57		64	60	57		63	59	57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	405982
5°	419815
10°	424071
15°	382007
20°	317458
25°	249053
30°	182275
35°	94185
40°	44728
45°	15741
50°	3555
55°	2313
60°	1622
65°	1221
70°	862
75°	570
80°	424
85°	0



TEST NUMBER: P857598

CATALOG NUMBER: LX4C30D010 EX4C309050 4LBMDLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	325.1	12.9
10°-20°	827.3	32.9
20°-30°	837.1	33.3
30°-40°	426.7	17.0
40°-50°	83.7	3.3
50°-60°	10.1	0.4
60°-70°	4.2	0.2
70°-80°	1.5	0.1
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1989.5	79.1
0°-40°	2416.3	96.0
0°-60°	2510.1	99.8
0°-90°	2516.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2516.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3305	
5°	3404	325
15°	3004	827
25°	1837	837
35°	628	427
45°	91	84
55°	11	10
65°	4	4
75°	1	2
85°	0	0
90°	0	



TEST NUMBER: P857598

CATALOG NUMBER: LX4C30D010 EX4C309050 4LBMDLI

CANDELA DISTRIBUTION (FULL):

0°	
0°	3304.6
2.5°	3335.2
5°	3404.2
7.5°	3443.7
10°	3399.4
12.5°	3250.0
15°	3003.5
17.5°	2712.5
20°	2428.2
22.5°	2133.7
25°	1837.3
27.5°	1542.2
30°	1284.9
32.5°	968.2
35°	628.0
37.5°	420.5
40°	278.9
42.5°	175.2
45°	90.6
47.5°	32.4
50°	18.6
52.5°	13.8
55°	10.8
57.5°	8.4
60°	6.6
62.5°	5.4
65°	4.2
67.5°	3.0
70°	2.4
72.5°	1.8
75°	1.2
77.5°	1.2
80°	0.6
82.5°	0.6
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)