

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857645

Luminaire Tested: **LX4C30D010 EX4C309835 4LBMLI**

Issue Date: 1/26/2022



Test Information

Test Method: LM-79-08
Report Number: P857645
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208279)
Test Lab: INNOVATION CENTER
Issue Date: 1/26/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309835 4LBMLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2492.4 lumens
Efficiency: N/A
Efficacy: 78.9 lumens/watt
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857645

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P857645

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95		
2	109	105	102	99	107	103	100	98	100	98	95	97	95	93	95	93	92	90		
3	105	99	95	92	103	98	94	91	95	92	89	93	90	88	91	89	87	85		
4	101	94	89	86	99	93	88	85	91	87	84	89	86	83	87	84	82	81		
5	96	89	84	80	95	88	84	80	87	82	79	85	81	79	83	80	78	77		
6	92	85	80	76	91	84	79	76	83	78	75	81	78	75	80	77	74	73		
7	89	81	76	72	88	80	75	72	79	75	71	78	74	71	77	73	71	69		
8	85	77	72	68	84	77	72	68	76	71	68	75	71	68	74	70	67	66		
9	82	74	69	65	81	73	68	65	72	68	65	72	68	65	71	67	64	63		
10	79	71	66	62	78	70	65	62	69	65	62	69	65	62	68	64	62	61		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	787982
5°	709106
10°	549705
15°	397880
20°	275504
25°	200837
30°	145930
35°	86356
40°	36325
45°	11328
50°	1472
55°	814
60°	934
65°	1105
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P857645

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	505.5	20.3
10°-20°	865.4	34.7
20°-30°	687.7	27.6
30°-40°	364.1	14.6
40°-50°	62.7	2.5
50°-60°	4.7	0.2
60°-70°	2.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2058.6	82.6
0°-40°	2422.6	97.2
0°-60°	2490.1	99.9
0°-90°	2492.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2492.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6414	
5°	5750	505
15°	3128	865
25°	1482	688
35°	576	364
45°	65	63
55°	4	5
65°	4	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P857645

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	6414.0
2.5°	6248.9
5°	5750.0
7.5°	5097.6
10°	4406.5
12.5°	3738.7
15°	3128.3
17.5°	2560.2
20°	2107.3
22.5°	1761.8
25°	1481.6
27.5°	1255.2
30°	1028.7
32.5°	798.4
35°	575.8
37.5°	380.1
40°	226.5
42.5°	130.6
45°	65.2
47.5°	23.1
50°	7.7
52.5°	7.7
55°	3.8
57.5°	3.8
60°	3.8
62.5°	3.8
65°	3.8
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)