

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857646

Luminaire Tested: **LX4C30D010 EX4C309835 4LBNH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857646
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309835 4LBNH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1660.5 lumens
Efficiency: N/A
Efficacy: 52.5 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857646

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P857646

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	256113
5°	250419
10°	231534
15°	207760
20°	182889
25°	157392
30°	126737
35°	84377
40°	43894
45°	19859
50°	8620
55°	5783
60°	3710
65°	2616
70°	2191
75°	1424
80°	0
85°	0



TEST NUMBER: P857646

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	188.1	11.3
10°-20°	456.2	27.5
20°-30°	529.7	31.9
30°-40°	350.8	21.1
40°-50°	98.4	5.9
50°-60°	24.7	1.5
60°-70°	9.3	0.6
70°-80°	3.2	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1174.1	70.7
0°-40°	1524.9	91.8
0°-60°	1648.0	99.2
0°-90°	1660.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1660.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2085	
5°	2031	188
15°	1634	456
25°	1161	530
35°	563	351
45°	114	98
55°	27	25
65°	9	9
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P857646

CATALOG NUMBER: LX4C30D010 EX4C309835 4LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	2084.7
2.5°	2075.7
5°	2030.6
7.5°	1952.3
10°	1856.0
12.5°	1747.7
15°	1633.5
17.5°	1522.1
20°	1398.9
22.5°	1284.6
25°	1161.1
27.5°	1043.9
30°	893.4
32.5°	734.0
35°	562.6
37.5°	403.2
40°	273.7
42.5°	177.5
45°	114.3
47.5°	69.3
50°	45.1
52.5°	33.1
55°	27.0
57.5°	21.1
60°	15.1
62.5°	12.0
65°	9.0
67.5°	6.1
70°	6.1
72.5°	3.0
75°	3.0
77.5°	3.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)