

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857662

Luminaire Tested: **LX4C30D010 EX4C309840 4LBSLI**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P857662
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309840 4LBSLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2725.2 lumens
Efficiency: N/A
Efficacy: 86.2 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857662

CATALOG NUMBER: LX4C30D010 EX4C309840 4LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P857662

CATALOG NUMBER: LX4C30D010 EX4C309840 4LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	112	108	105	102		109	106	103	101		102	100	98		98	96	95		95	93	92
2	104	98	93	88		102	96	91	87		93	89	85		90	86	84		87	84	82
3	97	89	82	77		95	87	81	77		84	79	75		82	78	74		79	76	73
4	90	81	73	68		88	79	73	68		77	71	67		75	70	66		73	69	65
5	84	73	66	61		82	72	65	60		70	64	60		69	63	59		67	62	59
6	79	67	60	54		77	66	59	54		65	58	54		63	58	53		62	57	53
7	74	62	54	49		72	61	54	49		60	53	49		58	53	48		57	52	48
8	69	57	50	45		68	57	50	45		55	49	45		54	49	44		53	48	44
9	65	53	46	41		64	53	46	41		52	45	41		51	45	41		50	44	41
10	61	50	43	38		60	49	42	38		48	42	38		47	42	38		46	41	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	239061
5°	233647
10°	219408
15°	204136
20°	189322
25°	172574
30°	153647
35°	136194
40°	122397
45°	109561
50°	93977
55°	75609
60°	56341
65°	35959
70°	17313
75°	2895
80°	2122
85°	0



TEST NUMBER: P857662

CATALOG NUMBER: LX4C30D010 EX4C309840 4LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	176.4	6.5
10°-20°	450.0	16.5
20°-30°	583.1	21.4
30°-40°	571.3	21.0
40°-50°	484.3	17.8
50°-60°	317.5	11.6
60°-70°	127.6	4.7
70°-80°	14.6	0.5
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1209.6	44.4
0°-40°	1780.9	65.3
0°-60°	2582.6	94.8
0°-90°	2725.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2725.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1946	
5°	1895	176
15°	1605	450
25°	1273	583
35°	908	571
45°	631	484
55°	353	317
65°	124	128
75°	6	15
85°	0	0
90°	0	



TEST NUMBER: P857662

CATALOG NUMBER: LX4C30D010 EX4C309840 4LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1945.9
2.5°	1930.7
5°	1894.6
7.5°	1834.2
10°	1758.8
12.5°	1677.4
15°	1605.0
17.5°	1526.6
20°	1448.1
22.5°	1363.7
25°	1273.1
27.5°	1179.6
30°	1083.1
32.5°	992.6
35°	908.1
37.5°	838.7
40°	763.2
42.5°	696.9
45°	630.6
47.5°	561.2
50°	491.7
52.5°	422.4
55°	353.0
57.5°	289.6
60°	229.3
62.5°	175.0
65°	123.7
67.5°	81.4
70°	48.2
72.5°	21.1
75°	6.1
77.5°	3.0
80°	3.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)