

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857672

Luminaire Tested: **LX4C30D010 EX4C309850 4LBNH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857672
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309850 4LBNH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1697.0 lumens
Efficiency: N/A
Efficacy: 53.7 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857672

CATALOG NUMBER: LX4C30D010 EX4C309850 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P857672

CATALOG NUMBER: LX4C30D010 EX4C309850 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	76	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	261752
5°	255932
10°	236636
15°	212326
20°	186903
25°	160848
30°	129531
35°	86236
40°	44857
45°	20310
50°	8811
55°	5912
60°	3784
65°	2703
70°	2227
75°	1471
80°	0
85°	0



TEST NUMBER: P857672

CATALOG NUMBER: LX4C30D010 EX4C309850 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	192.2	11.3
10°-20°	466.3	27.5
20°-30°	541.4	31.9
30°-40°	358.5	21.1
40°-50°	100.6	5.9
50°-60°	25.3	1.5
60°-70°	9.5	0.6
70°-80°	3.3	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1199.9	70.7
0°-40°	1558.4	91.8
0°-60°	1684.2	99.2
0°-90°	1697.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1697.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2131	
5°	2075	192
15°	1669	466
25°	1187	541
35°	575	359
45°	117	101
55°	28	25
65°	9	10
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P857672

CATALOG NUMBER: LX4C30D010 EX4C309850 4LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	2130.6
2.5°	2121.4
5°	2075.3
7.5°	1995.3
10°	1896.9
12.5°	1786.2
15°	1669.4
17.5°	1555.6
20°	1429.6
22.5°	1312.8
25°	1186.6
27.5°	1066.9
30°	913.1
32.5°	750.1
35°	575.0
37.5°	412.0
40°	279.7
42.5°	181.4
45°	116.9
47.5°	70.8
50°	46.1
52.5°	33.8
55°	27.6
57.5°	21.6
60°	15.4
62.5°	12.3
65°	9.3
67.5°	6.2
70°	6.2
72.5°	3.1
75°	3.1
77.5°	3.1
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)