

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857681

Luminaire Tested: **LX4C30D010 EX4C309030 4LBMDH**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P857681
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-9)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C30D010 EX4C309030 4LBMDH
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LRMD45 TRIM WITH H FINISH, DIM TO WARM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1922.0 lumens
Efficiency: N/A
Efficacy: 54.9 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.83
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 35
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857681

CATALOG NUMBER: LX4C30D010 EX4C309030 4LBMDH

Luminous Intensity Polar Plot





TEST NUMBER: P857681

CATALOG NUMBER: LX4C30D010 EX4C309030 4LBMDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	63	60	68	63	59		67	62	59		66
9	76	66	60	56	74	65	60	56	64	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	284443
5°	280596
10°	267449
15°	247468
20°	222777
25°	185085
30°	134525
35°	87211
40°	52779
45°	27208
50°	12309
55°	7411
60°	4963
65°	3546
70°	2694
75°	1804
80°	1132
85°	846



TEST NUMBER: P857681

CATALOG NUMBER: LX4C30D010 EX4C309030 4LBMDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	213.0	11.1
10°-20°	543.0	28.3
20°-30°	614.0	31.9
30°-40°	371.1	19.3
40°-50°	130.0	6.8
50°-60°	33.3	1.7
60°-70°	12.7	0.7
70°-80°	4.3	0.2
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1370.0	71.3
0°-40°	1741.0	90.6
0°-60°	1904.2	99.1
0°-90°	1922.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1922.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2315	
5°	2275	213
15°	1946	543
25°	1365	614
35°	582	371
45°	157	130
55°	35	33
65°	12	13
75°	4	4
85°	1	1
90°	0	



TEST NUMBER: P857681

CATALOG NUMBER: LX4C30D010 EX4C309030 4LBMDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	2315.3
2.5°	2305.7
5°	2275.3
7.5°	2221.6
10°	2143.9
12.5°	2050.1
15°	1945.7
17.5°	1831.3
20°	1704.0
22.5°	1548.0
25°	1365.4
27.5°	1156.1
30°	948.3
32.5°	749.8
35°	581.5
37.5°	440.9
40°	329.1
42.5°	236.4
45°	156.6
47.5°	96.4
50°	64.4
52.5°	46.4
55°	34.6
57.5°	26.6
60°	20.2
62.5°	16.0
65°	12.2
67.5°	9.6
70°	7.5
72.5°	5.3
75°	3.8
77.5°	2.7
80°	1.6
82.5°	1.1
85°	0.6
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)