

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857712

Luminaire Tested: **LD4C35D010 EU4359027 4LBMLI**

Issue Date: 7/19/2024



Test Information

Test Method: LM-79-08
Report Number: P857712
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER
Issue Date: 7/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C35D010 EU4359027 4LBMLI
Description: 4 INCH 3500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS
AND 4LBM TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3129.0 lumens
Efficiency: N/A
Efficacy: 77.5 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 40.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857712

CATALOG NUMBER: LD4C35D010 EU4359027 4LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P857712

CATALOG NUMBER: LD4C35D010 EU4359027 4LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	64		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		67
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	605999
5°	595698
10°	547347
15°	458383
20°	367230
25°	295074
30°	219654
35°	125485
40°	58889
45°	25001
50°	7970
55°	4048
60°	2801
65°	2209
70°	1365
75°	0
80°	0
85°	0



TEST NUMBER: P857712

CATALOG NUMBER: LD4C35D010 EU4359027 4LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	446.6	14.3
10°-20°	998.5	31.9
20°-30°	992.7	31.7
30°-40°	540.6	17.3
40°-50°	125.0	4.0
50°-60°	17.6	0.6
60°-70°	6.6	0.2
70°-80°	1.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2437.8	77.9
0°-40°	2978.4	95.2
0°-60°	3121.0	99.7
0°-90°	3129.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3129.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4933	
5°	4830	447
15°	3604	998
25°	2177	993
35°	837	541
45°	144	125
55°	19	18
65°	8	7
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P857712

CATALOG NUMBER: LD4C35D010 EU4359027 4LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	4932.7
2.5°	4921.3
5°	4830.4
7.5°	4645.0
10°	4387.6
12.5°	4009.0
15°	3604.0
17.5°	3202.7
20°	2808.9
22.5°	2487.2
25°	2176.8
27.5°	1881.5
30°	1548.4
32.5°	1177.4
35°	836.7
37.5°	564.0
40°	367.2
42.5°	230.9
45°	143.9
47.5°	83.3
50°	41.7
52.5°	22.7
55°	18.9
57.5°	11.4
60°	11.4
62.5°	7.6
65°	7.6
67.5°	3.8
70°	3.8
72.5°	3.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)