

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857859

Luminaire Tested: **LX4C35D010 EX4C359840 4LBMH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857859
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C35D010 EX4C359840 4LBMH
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2361.3 lumens
Efficiency: N/A
Efficacy: 58.4 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 40.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857859

CATALOG NUMBER: LX4C35D010 EX4C359840 4LBMH

Luminous Intensity Polar Plot





TEST NUMBER: P857859

CATALOG NUMBER: LX4C35D010 EX4C359840 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96
2	105	100	95	91	103	98	93	90	95	91	88		91	88	86		89
3	99	91	85	80	97	90	84	80	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	64	74	68	64		72	67	63		70
6	81	71	64	58	80	70	63	58	68	62	58		67	61	57		65
7	76	65	58	53	75	65	58	53	63	57	53		62	56	52		61
8	72	60	53	49	70	60	53	49	59	53	48		58	52	48		57
9	68	56	49	45	66	56	49	45	55	49	44		54	48	44		53
10	64	52	46	41	63	52	46	41	51	45	41		50	45	41		49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	186983
5°	187697
10°	188271
15°	188275
20°	187243
25°	182849
30°	170898
35°	147997
40°	115613
45°	82944
50°	53898
55°	32257
60°	18895
65°	12122
70°	8082
75°	6076
80°	4528
85°	0



TEST NUMBER: P857859

CATALOG NUMBER: LX4C35D010 EX4C359840 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	144.9	6.1
10°-20°	417.6	17.7
20°-30°	616.3	26.1
30°-40°	608.1	25.8
40°-50°	372.2	15.8
50°-60°	142.7	6.0
60°-70°	44.6	1.9
70°-80°	13.1	0.6
80°-90°	1.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1178.8	49.9
0°-40°	1787.0	75.7
0°-60°	2301.9	97.5
0°-90°	2361.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2361.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1522	
5°	1522	145
15°	1480	418
25°	1349	616
35°	987	608
45°	477	372
55°	151	143
65°	42	45
75°	13	13
85°	0	2
90°	0	



TEST NUMBER: P857859

CATALOG NUMBER: LX4C35D010 EX4C359840 4LBMH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1522.0
2.5°	1525.2
5°	1522.0
7.5°	1518.8
10°	1509.2
12.5°	1496.3
15°	1480.3
17.5°	1461.1
20°	1432.2
22.5°	1400.3
25°	1348.9
27.5°	1284.8
30°	1204.7
32.5°	1105.5
35°	986.8
37.5°	855.4
40°	720.9
42.5°	596.0
45°	477.4
47.5°	371.6
50°	282.0
52.5°	208.3
55°	150.6
57.5°	105.7
60°	76.9
62.5°	57.7
65°	41.7
67.5°	32.1
70°	22.5
72.5°	16.1
75°	12.8
77.5°	6.4
80°	6.4
82.5°	3.2
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)