

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857913

Luminaire Tested: **LX4C40D010 EX4C409030 4LBMDLI**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P857913
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-8)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C40D010 EX4C409030 4LBMDLI
Description: 4 INCH 4000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 4LRMD45 TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3325.0 lumens
Efficiency: N/A
Efficacy: 70.7 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.82
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857913

CATALOG NUMBER: LX4C40D010 EX4C409030 4LBMDLI

Luminous Intensity Polar Plot





TEST NUMBER: P857913

CATALOG NUMBER: LX4C40D010 EX4C409030 4LBMDLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	63		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		66
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		63

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	536513
5°	554792
10°	560421
15°	504832
20°	419538
25°	329138
30°	240877
35°	124480
40°	59114
45°	20797
50°	4702
55°	3063
60°	2138
65°	1599
70°	1149
75°	759
80°	566
85°	0



TEST NUMBER: P857913

CATALOG NUMBER: LX4C40D010 EX4C409030 4LBMDLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	429.7	12.9
10°-20°	1093.3	32.9
20°-30°	1106.3	33.3
30°-40°	564.0	17.0
40°-50°	110.6	3.3
50°-60°	13.4	0.4
60°-70°	5.6	0.2
70°-80°	2.0	0.1
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2629.2	79.1
0°-40°	3193.2	96.0
0°-60°	3317.1	99.8
0°-90°	3325.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3325.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4367	
5°	4499	430
15°	3969	1093
25°	2428	1106
35°	830	564
45°	120	111
55°	14	13
65°	6	6
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P857913

CATALOG NUMBER: LX4C40D010 EX4C409030 4LBMDLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	4367.1
2.5°	4407.6
5°	4498.7
7.5°	4551.1
10°	4492.4
12.5°	4295.0
15°	3969.2
17.5°	3584.7
20°	3209.0
22.5°	2819.7
25°	2428.1
27.5°	2038.1
30°	1698.0
32.5°	1279.5
35°	830.0
37.5°	555.7
40°	368.6
42.5°	231.5
45°	119.7
47.5°	42.8
50°	24.6
52.5°	18.2
55°	14.3
57.5°	11.1
60°	8.7
62.5°	7.1
65°	5.5
67.5°	4.0
70°	3.2
72.5°	2.4
75°	1.6
77.5°	1.6
80°	0.8
82.5°	0.8
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)