

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P857958

Luminaire Tested: **LX4C40D010 EX4C409040 4LBNH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P857958
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C40D010 EX4C409040 4LBNH
Description: 4 INCH 4000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 4LBN TRIM WITH H FINISH
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2554.0 lumens
Efficiency: N/A
Efficacy: 54.3 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P857958

CATALOG NUMBER: LX4C40D010 EX4C409040 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P857958

CATALOG NUMBER: LX4C40D010 EX4C409040 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	393954
5°	385174
10°	356145
15°	319571
20°	281309
25°	242099
30°	194957
35°	129790
40°	67517
45°	30561
50°	13264
55°	8889
60°	5700
65°	4041
70°	3341
75°	2183
80°	0
85°	0



TEST NUMBER: P857958

CATALOG NUMBER: LX4C40D010 EX4C409040 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	289.3	11.3
10°-20°	701.8	27.5
20°-30°	814.8	31.9
30°-40°	539.6	21.1
40°-50°	151.3	5.9
50°-60°	38.0	1.5
60°-70°	14.3	0.6
70°-80°	4.9	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1805.9	70.7
0°-40°	2345.5	91.8
0°-60°	2534.8	99.2
0°-90°	2554.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2554.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3207	
5°	3123	289
15°	2513	702
25°	1786	815
35°	865	540
45°	176	151
55°	42	38
65°	14	14
75°	5	5
85°	0	0
90°	0	



TEST NUMBER: P857958

CATALOG NUMBER: LX4C40D010 EX4C409040 4LBNH

CANDELA DISTRIBUTION (FULL):

0°	
0°	3206.7
2.5°	3192.7
5°	3123.3
7.5°	3002.9
10°	2854.9
12.5°	2688.2
15°	2512.6
17.5°	2341.3
20°	2151.7
22.5°	1975.8
25°	1786.0
27.5°	1605.6
30°	1374.3
32.5°	1129.0
35°	865.4
37.5°	620.1
40°	421.0
42.5°	272.9
45°	175.9
47.5°	106.5
50°	69.4
52.5°	50.8
55°	41.5
57.5°	32.5
60°	23.2
62.5°	18.6
65°	13.9
67.5°	9.3
70°	9.3
72.5°	4.6
75°	4.6
77.5°	4.6
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)