

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858012

Luminaire Tested: **LX4C40D010 EX4C409830 4LBNLI**

Issue Date: 1/21/2022



Test Information

Test Method: LM-79-08
Report Number: P858012
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208279)
Test Lab: INNOVATION CENTER
Issue Date: 1/21/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C40D010 EX4C409830 4LBNI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2642.2 lumens
Efficiency: N/A
Efficacy: 56.2 lumens/watt
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858012

CATALOG NUMBER: LX4C40D010 EX4C409830 4LBNLI

Luminous Intensity Polar Plot





TEST NUMBER: P858012

CATALOG NUMBER: LX4C40D010 EX4C409830 4LBNLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	92	103	98	94	91	95	92	89		93	90	88		91
4	101	94	89	86	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	84	80	87	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	78	75		80
7	89	81	76	72	88	80	75	72	79	75	71		78	74	71		77
8	85	77	72	68	84	77	72	68	76	71	68		75	71	68		74
9	82	74	69	65	81	73	68	65	72	68	65		72	68	65		71
10	79	71	66	62	78	70	65	62	69	65	62		69	65	62		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	835354
5°	751739
10°	582763
15°	421791
20°	292055
25°	212914
30°	154711
35°	91546
40°	38506
45°	12006
50°	1548
55°	878
60°	1007
65°	1192
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P858012

CATALOG NUMBER: LX4C40D010 EX4C409830 4LBNLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	535.9	20.3
10°-20°	917.4	34.7
20°-30°	729.1	27.6
30°-40°	386.0	14.6
40°-50°	66.5	2.5
50°-60°	5.0	0.2
60°-70°	2.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2182.3	82.6
0°-40°	2568.3	97.2
0°-60°	2639.7	99.9
0°-90°	2642.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2642.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6800	
5°	6096	536
15°	3316	917
25°	1571	729
35°	610	386
45°	69	66
55°	4	5
65°	4	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P858012

CATALOG NUMBER: LX4C40D010 EX4C409830 4LBNLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	6799.6
2.5°	6624.5
5°	6095.7
7.5°	5404.0
10°	4671.5
12.5°	3963.4
15°	3316.3
17.5°	2714.1
20°	2233.9
22.5°	1867.7
25°	1570.7
27.5°	1330.7
30°	1090.6
32.5°	846.4
35°	610.4
37.5°	402.9
40°	240.1
42.5°	138.4
45°	69.1
47.5°	24.4
50°	8.1
52.5°	8.1
55°	4.1
57.5°	4.1
60°	4.1
62.5°	4.1
65°	4.1
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)