

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858030

Luminaire Tested: **LX4C40D010 EX4C409835 4LBWLI**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P858030
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C40D010 EX4C409835 4LBWLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3603.5 lumens
Efficiency: N/A
Efficacy: 76.7 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858030

CATALOG NUMBER: LX4C40D010 EX4C409835 4LBWLI

Luminous Intensity Polar Plot





TEST NUMBER: P858030

CATALOG NUMBER: LX4C40D010 EX4C409835 4LBWLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	106	101	97	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	87	83	98	92	86	82	89	85	81		86	83	80		84
4	94	86	79	75	92	84	79	74	82	77	73		80	76	72		78
5	88	79	72	68	87	78	72	67	76	71	67		74	70	66		73
6	83	73	66	62	82	72	66	61	71	65	61		69	64	60		68
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59
9	69	59	52	48	68	58	52	47	57	51	47		56	51	47		55
10	66	55	48	44	65	54	48	44	53	48	44		53	47	44		52

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P858030

CATALOG NUMBER: LX4C40D010 EX4C409835 4LBWL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	215.9	6.0
10°-20°	681.4	18.9
20°-30°	1063.0	29.5
30°-40°	1034.3	28.7
40°-50°	516.6	14.3
50°-60°	80.0	2.2
60°-70°	9.7	0.3
70°-80°	2.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1960.3	54.4
0°-40°	2994.6	83.1
0°-60°	3591.1	99.7
0°-90°	3603.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3603.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2208	
5°	2237	216
15°	2406	681
25°	2336	1063
35°	1680	1034
45°	648	517
55°	66	80
65°	8	10
75°	4	3
85°	0	0
90°	0	



TEST NUMBER: P858030

CATALOG NUMBER: LX4C40D010 EX4C409835 4LBWLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2207.9
2.5°	2216.2
5°	2236.8
7.5°	2269.8
10°	2311.1
12.5°	2364.7
15°	2406.0
17.5°	2439.1
20°	2443.2
22.5°	2414.3
25°	2335.9
27.5°	2220.3
30°	2075.8
32.5°	1894.4
35°	1679.7
37.5°	1444.4
40°	1196.8
42.5°	932.8
45°	648.0
47.5°	416.8
50°	251.6
52.5°	136.2
55°	66.1
57.5°	28.9
60°	16.5
62.5°	12.4
65°	8.3
67.5°	8.3
70°	4.1
72.5°	4.1
75°	4.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)