

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858040

Luminaire Tested: **LX4C40D010 EX4C409840 4LBSLI**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P858040
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C40D010 EX4C409840 4LBSLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3733.7 lumens
Efficiency: N/A
Efficacy: 79.4 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858040

CATALOG NUMBER: LX4C40D010 EX4C409840 4LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P858040

CATALOG NUMBER: LX4C40D010 EX4C409840 4LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	98		98	96	95		95
2	104	98	93	88	102	96	91	87	93	89	85		90	86	84		87
3	97	89	82	77	95	87	81	77	84	79	75		82	78	74		79
4	90	81	73	68	88	79	73	68	77	71	67		75	70	66		73
5	84	73	66	61	82	72	65	60	70	64	60		69	63	59		67
6	79	67	60	54	77	66	59	54	65	58	54		63	58	53		62
7	74	62	54	49	72	61	54	49	60	53	49		58	53	48		57
8	69	57	50	45	68	57	50	45	55	49	45		54	49	44		53
9	65	53	46	41	64	53	46	41	52	45	41		51	45	41		50
10	61	50	43	38	60	49	42	38	48	42	38		47	42	38		46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	327527
5°	320109
10°	300607
15°	279672
20°	259384
25°	236447
30°	210505
35°	186586
40°	167703
45°	150095
50°	128762
55°	103582
60°	77177
65°	49273
70°	23743
75°	3940
80°	2901
85°	0



TEST NUMBER: P858040

CATALOG NUMBER: LX4C40D010 EX4C409840 4LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	241.7	6.5
10°-20°	616.5	16.5
20°-30°	798.9	21.4
30°-40°	782.8	21.0
40°-50°	663.5	17.8
50°-60°	434.9	11.6
60°-70°	174.8	4.7
70°-80°	20.0	0.5
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1657.2	44.4
0°-40°	2439.9	65.3
0°-60°	3538.4	94.8
0°-90°	3733.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3733.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2666	
5°	2596	242
15°	2199	617
25°	1744	799
35°	1244	783
45°	864	663
55°	484	435
65°	170	175
75°	8	20
85°	0	1
90°	0	



TEST NUMBER: P858040

CATALOG NUMBER: LX4C40D010 EX4C409840 4LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2666.0
2.5°	2645.4
5°	2595.7
7.5°	2513.0
10°	2409.7
12.5°	2298.1
15°	2198.9
17.5°	2091.5
20°	1984.0
22.5°	1868.3
25°	1744.3
27.5°	1616.1
30°	1483.9
32.5°	1359.9
35°	1244.1
37.5°	1149.1
40°	1045.7
42.5°	954.8
45°	863.9
47.5°	768.8
50°	673.7
52.5°	578.7
55°	483.6
57.5°	396.8
60°	314.1
62.5°	239.7
65°	169.5
67.5°	111.6
70°	66.1
72.5°	28.9
75°	8.3
77.5°	4.1
80°	4.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)