

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858482

Luminaire Tested: **LD4C20W2N2765D010 4LBMH_3000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858482
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20W2N2765D010 4LBMH_3000K
Description: 4 INCH 2000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, W2N2765 LEDS
AND 4LBMH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1567.0 lumens
Efficiency: N/A
Efficacy: 61.7 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 25.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858482

CATALOG NUMBER: LD4C20W2N2765D010 4LBMH_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P858482

CATALOG NUMBER: LD4C20W2N2765D010 4LBMH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	190890
5°	188117
10°	180249
15°	170253
20°	158925
25°	144256
30°	120452
35°	87256
40°	54623
45°	31221
50°	16284
55°	9124
60°	5823
65°	3430
70°	2550
75°	1139
80°	1698
85°	0



TEST NUMBER: P858482

CATALOG NUMBER: LD4C20W2N2765D010 4LBMH_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	143.0	9.1
10°-20°	375.1	23.9
20°-30°	482.0	30.8
30°-40°	362.7	23.1
40°-50°	145.7	9.3
50°-60°	41.4	2.6
60°-70°	13.1	0.8
70°-80°	3.8	0.2
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1000.1	63.8
0°-40°	1362.8	87.0
0°-60°	1549.8	98.9
0°-90°	1567.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1567.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1554	
5°	1525	143
15°	1339	375
25°	1064	482
35°	582	363
45°	180	146
55°	43	41
65°	12	13
75°	2	4
85°	0	0
90°	0	



TEST NUMBER: P858482

CATALOG NUMBER: LD4C20W2N2765D010 4LBMH_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1553.8
2.5°	1544.3
5°	1525.4
7.5°	1489.9
10°	1444.9
12.5°	1390.6
15°	1338.6
17.5°	1279.4
20°	1215.6
22.5°	1147.1
25°	1064.2
27.5°	964.9
30°	849.1
32.5°	718.9
35°	581.8
37.5°	454.0
40°	340.6
42.5°	250.7
45°	179.7
47.5°	123.0
50°	85.2
52.5°	59.1
55°	42.6
57.5°	30.8
60°	23.7
62.5°	16.6
65°	11.8
67.5°	9.5
70°	7.1
72.5°	4.7
75°	2.4
77.5°	2.4
80°	2.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)