

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858492

Luminaire Tested: **LD4C20W2N2765D010 4LBMLI_6500K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858492
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C20W2N2765D010 4LBMLI_6500K
Description: 4 INCH 2000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 6500K, W2N2765 LEDS
AND 4LBMLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1997.0 lumens
Efficiency: N/A
Efficacy: 78.6 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 25.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858492

CATALOG NUMBER: LD4C20W2N2765D010 4LBMLI_6500K

Luminous Intensity Polar Plot





TEST NUMBER: P858492

CATALOG NUMBER: LD4C20W2N2765D010 4LBMLI_6500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	64		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		67
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	386755
5°	380192
10°	349334
15°	292543
20°	234374
25°	188325
30°	140185
35°	80087
40°	37592
45°	15967
50°	5084
55°	2592
60°	1794
65°	1395
70°	862
75°	0
80°	0
85°	0



TEST NUMBER: P858492

CATALOG NUMBER: LD4C20W2N2765D010 4LBMLI_6500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	285.0	14.3
10°-20°	637.3	31.9
20°-30°	633.6	31.7
30°-40°	345.0	17.3
40°-50°	79.8	4.0
50°-60°	11.3	0.6
60°-70°	4.2	0.2
70°-80°	0.9	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1555.9	77.9
0°-40°	1900.9	95.2
0°-60°	1991.9	99.7
0°-90°	1997.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1997.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3148	
5°	3083	285
15°	2300	637
25°	1389	634
35°	534	345
45°	92	80
55°	12	11
65°	5	4
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P858492

CATALOG NUMBER: LD4C20W2N2765D010 4LBMLI_6500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	3148.1
2.5°	3140.9
5°	3082.9
7.5°	2964.5
10°	2800.3
12.5°	2558.7
15°	2300.1
17.5°	2044.0
20°	1792.7
22.5°	1587.4
25°	1389.3
27.5°	1200.8
30°	988.2
32.5°	751.4
35°	534.0
37.5°	360.0
40°	234.4
42.5°	147.3
45°	91.9
47.5°	53.2
50°	26.6
52.5°	14.5
55°	12.1
57.5°	7.3
60°	7.3
62.5°	4.8
65°	4.8
67.5°	2.4
70°	2.4
72.5°	2.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)