

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858601

Luminaire Tested: **LD4C25W2N2765D010 4LBWLI_2700K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858601
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C25W2N2765D010 4LBWLI_2700K
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, W2N2765 LEDS
AND 4LBWLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2254.0 lumens
Efficiency: N/A
Efficacy: 67.3 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 33.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858601

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P858601

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	106	101	97	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	87	83	98	92	86	82	89	85	81		86	83	80		84
4	94	86	79	75	92	84	79	74	82	77	73		80	76	72		78
5	88	79	72	68	87	78	72	67	76	71	67		74	70	66		73
6	83	73	66	62	82	72	66	61	71	65	61		69	64	60		68
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59
9	69	59	52	48	68	58	52	47	57	51	47		56	51	47		55
10	66	55	48	44	65	54	48	44	53	48	44		53	47	44		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	169661
5°	172541
10°	180337
15°	191417
20°	199794
25°	198058
30°	184190
35°	157580
40°	120056
45°	70417
50°	30083
55°	8867
60°	2531
65°	1512
70°	934
75°	1234
80°	0
85°	0



TEST NUMBER: P858601

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	135.1	6.0
10°-20°	426.2	18.9
20°-30°	664.9	29.5
30°-40°	646.9	28.7
40°-50°	323.1	14.3
50°-60°	50.0	2.2
60°-70°	6.1	0.3
70°-80°	1.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1226.2	54.4
0°-40°	1873.1	83.1
0°-60°	2246.2	99.7
0°-90°	2254.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2254.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1381	
5°	1399	135
15°	1505	426
25°	1461	665
35°	1051	647
45°	405	323
55°	41	50
65°	5	6
75°	3	2
85°	0	0
90°	0	



TEST NUMBER: P858601

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_2700K

CANDELA DISTRIBUTION (FULL):

	0°
0°	1381.0
2.5°	1386.2
5°	1399.1
7.5°	1419.8
10°	1445.6
12.5°	1479.1
15°	1505.0
17.5°	1525.6
20°	1528.2
22.5°	1510.1
25°	1461.1
27.5°	1388.8
30°	1298.4
32.5°	1184.9
35°	1050.7
37.5°	903.4
40°	748.6
42.5°	583.4
45°	405.3
47.5°	260.7
50°	157.4
52.5°	85.2
55°	41.4
57.5°	18.1
60°	10.3
62.5°	7.8
65°	5.2
67.5°	5.2
70°	2.6
72.5°	2.6
75°	2.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)