

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858603

Luminaire Tested: **LD4C25W2N2765D010 4LBWLI_3500K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858603
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208077)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C25W2N2765D010 4LBWLI_3500K
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, W2N2765 LEDS
AND 4LBWLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2582.0 lumens
Efficiency: N/A
Efficacy: 77.1 lumens/watt
Spacing Criteria (0/90/45): 1.29 / 1.29 / 1.18
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 33.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858603

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P858603

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	107	105		110	108	105	103		104	102	100		100	98	97		96	95	94
2	106	101	97	93		104	99	95	92		96	93	90		93	90	88		90	88	86
3	100	93	87	83		98	92	86	82		89	85	81		86	83	80		84	81	78
4	94	86	79	75		92	84	79	74		82	77	73		80	76	72		78	75	72
5	88	79	72	68		87	78	72	67		76	71	67		74	70	66		73	69	65
6	83	73	66	62		82	72	66	61		71	65	61		69	64	60		68	63	60
7	78	68	61	56		77	67	61	56		66	60	56		64	59	55		63	59	55
8	74	63	56	52		72	62	56	51		61	55	51		60	55	51		59	54	51
9	69	59	52	48		68	58	52	47		57	51	47		56	51	47		55	50	47
10	66	55	48	44		65	54	48	44		53	48	44		53	47	44		52	47	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	194354
5°	197649
10°	206584
15°	219271
20°	228870
25°	226890
30°	211001
35°	180497
40°	137521
45°	80668
50°	34460
55°	10153
60°	2899
65°	1715
70°	1078
75°	1424
80°	0
85°	0



TEST NUMBER: P858603

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.7	6.0
10°-20°	488.2	18.9
20°-30°	761.7	29.5
30°-40°	741.1	28.7
40°-50°	370.1	14.3
50°-60°	57.3	2.2
60°-70°	6.9	0.3
70°-80°	2.0	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1404.6	54.4
0°-40°	2145.7	83.1
0°-60°	2573.1	99.7
0°-90°	2582.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2582.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1582	
5°	1603	155
15°	1724	488
25°	1674	762
35°	1204	741
45°	464	370
55°	47	57
65°	6	7
75°	3	2
85°	0	0
90°	0	



TEST NUMBER: P858603

CATALOG NUMBER: LD4C25W2N2765D010 4LBWLI_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1582.0
2.5°	1587.9
5°	1602.7
7.5°	1626.4
10°	1656.0
12.5°	1694.4
15°	1724.0
17.5°	1747.6
20°	1750.6
22.5°	1729.9
25°	1673.8
27.5°	1590.9
30°	1487.4
32.5°	1357.4
35°	1203.5
37.5°	1034.9
40°	857.5
42.5°	668.3
45°	464.3
47.5°	298.6
50°	180.3
52.5°	97.6
55°	47.4
57.5°	20.7
60°	11.8
62.5°	8.9
65°	5.9
67.5°	5.9
70°	3.0
72.5°	3.0
75°	3.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)