

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858622

Luminaire Tested: **LD4C30W2N2050D010 4LBNH_3500K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858622
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203666)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2050D010 4LBNH_3500K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, W2N2050 LEDS
AND 4LBNH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2106.0 lumens
Efficiency: N/A
Efficacy: 53.2 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.84
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858622

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P858622

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	104	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	57	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	331668
5°	323451
10°	298461
15°	264244
20°	229432
25°	196241
30°	161790
35°	106543
40°	57269
45°	25349
50°	10283
55°	7411
60°	4718
65°	3372
70°	2766
75°	1851
80°	2759
85°	0



TEST NUMBER: P858622

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	242.8	11.5
10°-20°	578.9	27.5
20°-30°	663.2	31.5
30°-40°	445.6	21.2
40°-50°	127.3	6.0
50°-60°	31.2	1.5
60°-70°	11.8	0.6
70°-80°	4.6	0.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1484.9	70.5
0°-40°	1930.6	91.7
0°-60°	2089.0	99.2
0°-90°	2106.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2106.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2700	
5°	2623	243
15°	2078	579
25°	1448	663
35°	710	446
45°	146	127
55°	35	31
65°	12	12
75°	4	5
85°	0	1
90°	0	



TEST NUMBER: P858622

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2699.7
2.5°	2680.5
5°	2622.8
7.5°	2519.1
10°	2392.5
12.5°	2231.1
15°	2077.6
17.5°	1916.3
20°	1754.9
22.5°	1601.4
25°	1447.7
27.5°	1305.6
30°	1140.5
32.5°	921.6
35°	710.4
37.5°	518.4
40°	357.1
42.5°	234.2
45°	145.9
47.5°	88.3
50°	53.8
52.5°	42.2
55°	34.6
57.5°	26.9
60°	19.2
62.5°	15.3
65°	11.6
67.5°	7.7
70°	7.7
72.5°	3.9
75°	3.9
77.5°	3.9
80°	3.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)