

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858623

Luminaire Tested: **LD4C30W2N2050D010 4LBNH_4000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858623
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P203666)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2050D010 4LBNH_4000K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, W2N2050 LEDS
AND 4LBNH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2043.0 lumens
Efficiency: N/A
Efficacy: 51.6 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.84
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858623

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_4000K

Luminous Intensity Polar Plot





TEST NUMBER: P858623

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	104	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	57	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	321741
5°	313782
10°	289529
15°	256333
20°	222568
25°	190372
30°	156953
35°	103364
40°	55570
45°	24602
50°	9977
55°	7197
60°	4570
65°	3256
70°	2694
75°	1756
80°	2618
85°	0



TEST NUMBER: P858623

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	235.5	11.5
10°-20°	561.6	27.5
20°-30°	643.4	31.5
30°-40°	432.3	21.2
40°-50°	123.5	6.0
50°-60°	30.2	1.5
60°-70°	11.5	0.6
70°-80°	4.4	0.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1440.5	70.5
0°-40°	1872.8	91.7
0°-60°	2026.6	99.2
0°-90°	2043.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2043.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2619	
5°	2544	236
15°	2015	562
25°	1404	643
35°	689	432
45°	142	124
55°	34	30
65°	11	11
75°	4	4
85°	0	1
90°	0	



TEST NUMBER: P858623

CATALOG NUMBER: LD4C30W2N2050D010 4LBNH_4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2618.9
2.5°	2600.3
5°	2544.4
7.5°	2443.8
10°	2320.9
12.5°	2164.3
15°	2015.4
17.5°	1859.0
20°	1702.4
22.5°	1553.5
25°	1404.4
27.5°	1266.6
30°	1106.4
32.5°	894.0
35°	689.2
37.5°	502.9
40°	346.5
42.5°	227.2
45°	141.6
47.5°	85.6
50°	52.2
52.5°	40.9
55°	33.6
57.5°	26.1
60°	18.6
62.5°	14.9
65°	11.2
67.5°	7.5
70°	7.5
72.5°	3.7
75°	3.7
77.5°	3.7
80°	3.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)