

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858650

Luminaire Tested: **LD4C30W2N2765D010 4LBMH_3000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858650
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2765D010 4LBMH_3000K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, W2N2765 LEDS
AND 4LBMH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2580.0 lumens
Efficiency: N/A
Efficacy: 65.2 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858650

CATALOG NUMBER: LD4C30W2N2765D010 4LBMH_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P858650

CATALOG NUMBER: LD4C30W2N2765D010 4LBMH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	314284
5°	309725
10°	296777
15°	280308
20°	261659
25°	237517
30°	198305
35°	143662
40°	89938
45°	51410
50°	26796
55°	15015
60°	9583
65°	5669
70°	4203
75°	1851
80°	2759
85°	0



TEST NUMBER: P858650

CATALOG NUMBER: LD4C30W2N2765D010 4LBMH_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	235.4	9.1
10°-20°	617.5	23.9
20°-30°	793.7	30.8
30°-40°	597.1	23.1
40°-50°	239.8	9.3
50°-60°	68.2	2.6
60°-70°	21.6	0.8
70°-80°	6.2	0.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1646.6	63.8
0°-40°	2243.7	87.0
0°-60°	2551.7	98.9
0°-90°	2580.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2580.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2558	
5°	2512	235
15°	2204	618
25°	1752	794
35°	958	597
45°	296	240
55°	70	68
65°	20	22
75°	4	6
85°	0	1
90°	0	



TEST NUMBER: P858650

CATALOG NUMBER: LD4C30W2N2765D010 4LBMH_3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2558.2
2.5°	2542.6
5°	2511.5
7.5°	2453.1
10°	2379.0
12.5°	2289.6
15°	2203.9
17.5°	2106.5
20°	2001.4
22.5°	1888.6
25°	1752.2
27.5°	1588.6
30°	1397.9
32.5°	1183.7
35°	957.9
37.5°	747.6
40°	560.8
42.5°	412.7
45°	295.9
47.5°	202.6
50°	140.2
52.5°	97.4
55°	70.1
57.5°	50.6
60°	39.0
62.5°	27.3
65°	19.5
67.5°	15.6
70°	11.7
72.5°	7.8
75°	3.9
77.5°	3.9
80°	3.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)