

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858657

Luminaire Tested: **LD4C30W2N2765D010 4LBMLI_3500K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858657
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2765D010 4LBMLI_3500K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, W2N2765 LEDS
AND 4LBMLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3162.0 lumens
Efficiency: N/A
Efficacy: 79.8 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858657

CATALOG NUMBER: LD4C30W2N2765D010 4LBMLI_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P858657

CATALOG NUMBER: LD4C30W2N2765D010 4LBMLI_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	64		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		67
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	612388
5°	601988
10°	553123
15°	463216
20°	371113
25°	298178
30°	221967
35°	126805
40°	59515
45°	25262
50°	8046
55°	4091
60°	2826
65°	2238
70°	1365
75°	0
80°	0
85°	0



TEST NUMBER: P858657

CATALOG NUMBER: LD4C30W2N2765D010 4LBMLI_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	451.3	14.3
10°-20°	1009.0	31.9
20°-30°	1003.2	31.7
30°-40°	546.3	17.3
40°-50°	126.3	4.0
50°-60°	17.8	0.6
60°-70°	6.6	0.2
70°-80°	1.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2463.5	77.9
0°-40°	3009.8	95.2
0°-60°	3153.9	99.7
0°-90°	3162.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3162.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4985	
5°	4881	451
15°	3642	1009
25°	2200	1003
35°	846	546
45°	145	126
55°	19	18
65°	8	7
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P858657

CATALOG NUMBER: LD4C30W2N2765D010 4LBMLI_3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	4984.7
2.5°	4973.2
5°	4881.4
7.5°	4694.0
10°	4433.9
12.5°	4051.3
15°	3642.0
17.5°	3236.4
20°	2838.6
22.5°	2513.4
25°	2199.7
27.5°	1901.4
30°	1564.7
32.5°	1189.8
35°	845.5
37.5°	569.9
40°	371.1
42.5°	233.3
45°	145.4
47.5°	84.2
50°	42.1
52.5°	23.0
55°	19.1
57.5°	11.5
60°	11.5
62.5°	7.7
65°	7.7
67.5°	3.8
70°	3.8
72.5°	3.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)