

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858668

Luminaire Tested: **LD4C30W2N2765D010 4LBNLI_3000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858668
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208279)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2765D010 4LBNLI_3000K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, W2N2765 LEDS
AND 4LBNLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2526.0 lumens
Efficiency: N/A
Efficacy: 63.8 lumens/watt
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858668

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P858668

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	92	103	98	94	91	95	92	89		93	90	88		91
4	101	94	89	86	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	84	80	87	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	78	75		80
7	89	81	76	72	88	80	75	72	79	75	71		78	74	71		77
8	85	77	72	68	84	77	72	68	76	71	68		75	71	68		74
9	82	74	69	65	81	73	68	65	72	68	65		72	68	65		71
10	79	71	66	62	78	70	65	62	69	65	62		69	65	62		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	798609
5°	718663
10°	557115
15°	403247
20°	279217
25°	203548
30°	147902
35°	87511
40°	36806
45°	11484
50°	1491
55°	835
60°	958
65°	1134
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P858668

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	512.3	20.3
10°-20°	877.0	34.7
20°-30°	697.0	27.6
30°-40°	369.0	14.6
40°-50°	63.6	2.5
50°-60°	4.8	0.2
60°-70°	2.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2086.3	82.6
0°-40°	2455.3	97.2
0°-60°	2523.6	99.9
0°-90°	2526.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2526.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6500	
5°	5828	512
15°	3170	877
25°	1502	697
35°	584	369
45°	66	64
55°	4	5
65°	4	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P858668

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	6500.5
2.5°	6333.1
5°	5827.5
7.5°	5166.2
10°	4465.9
12.5°	3789.1
15°	3170.5
17.5°	2594.7
20°	2135.7
22.5°	1785.5
25°	1501.6
27.5°	1272.1
30°	1042.6
32.5°	809.2
35°	583.5
37.5°	385.2
40°	229.5
42.5°	132.3
45°	66.1
47.5°	23.4
50°	7.8
52.5°	7.8
55°	3.9
57.5°	3.9
60°	3.9
62.5°	3.9
65°	3.9
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)