

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858669

Luminaire Tested: **LD4C30W2N2765D010 4LBNLI_3500K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858669
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208279)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C30W2N2765D010 4LBNLI_3500K
Description: 4 INCH 3000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, W2N2765 LEDS
AND 4LBNLI TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2481.0 lumens
Efficiency: N/A
Efficacy: 62.7 lumens/watt
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858669

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P858669

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			50
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			102
1	114	112	110	108		112	110	108	106		106	104	103			102	101	100			99
2	109	105	102	99		107	103	100	98		100	98	95			97	95	93			95
3	105	99	95	92		103	98	94	91		95	92	89			93	90	88			91
4	101	94	89	86		99	93	88	85		91	87	84			89	86	83			87
5	96	89	84	80		95	88	84	80		87	82	79			85	81	79			83
6	92	85	80	76		91	84	79	76		83	78	75			81	78	75			80
7	89	81	76	72		88	80	75	72		79	75	71			78	74	71			77
8	85	77	72	68		84	77	72	68		76	71	68			75	71	68			74
9	82	74	69	65		81	73	68	65		72	68	65			72	68	65			71
10	79	71	66	62		78	70	65	62		69	65	62			69	65	62			68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	784383
5°	705862
10°	547198
15°	396061
20°	274236
25°	199928
30°	145264
35°	85966
40°	36148
45°	11276
50°	1472
55°	814
60°	934
65°	1105
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P858669

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	503.2	20.3
10°-20°	861.4	34.7
20°-30°	684.6	27.6
30°-40°	362.4	14.6
40°-50°	62.4	2.5
50°-60°	4.7	0.2
60°-70°	2.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2049.2	82.6
0°-40°	2411.6	97.2
0°-60°	2478.7	99.9
0°-90°	2481.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2481.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6385	
5°	5724	503
15°	3114	861
25°	1475	685
35°	573	362
45°	65	62
55°	4	5
65°	4	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P858669

CATALOG NUMBER: LD4C30W2N2765D010 4LBNLI_3500K

CANDELA DISTRIBUTION (FULL):

	0°
0°	6384.7
2.5°	6220.3
5°	5723.7
7.5°	5074.2
10°	4386.4
12.5°	3721.6
15°	3114.0
17.5°	2548.5
20°	2097.6
22.5°	1753.7
25°	1474.9
27.5°	1249.5
30°	1024.0
32.5°	794.8
35°	573.2
37.5°	378.3
40°	225.4
42.5°	129.9
45°	64.9
47.5°	23.0
50°	7.7
52.5°	7.7
55°	3.8
57.5°	3.8
60°	3.8
62.5°	3.8
65°	3.8
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)