

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P858693

Luminaire Tested: **LD4C35W2N2050D010 4LBMH_3000K**

Issue Date: 11/9/2023



Test Information

Test Method: LM-79-08
Report Number: P858693
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 11/9/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C35W2N2050D010 4LBMH_3000K
Description: 4 INCH 3500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, W2N2050 LEDS
AND 4LBMH TRIM WITH FINISH

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2857.0 lumens
Efficiency: N/A
Efficacy: 54.1 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 52.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P858693

CATALOG NUMBER: LD4C35W2N2050D010 4LBMH_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P858693

CATALOG NUMBER: LD4C35W2N2050D010 4LBMH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	348032
5°	342973
10°	328650
15°	310401
20°	289741
25°	263029
30°	219598
35°	159095
40°	99592
45°	56918
50°	29682
55°	16621
60°	10590
65°	6279
70°	4634
75°	2041
80°	3042
85°	0



TEST NUMBER: P858693

CATALOG NUMBER: LD4C35W2N2050D010 4LBMH_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	260.7	9.1
10°-20°	683.9	23.9
20°-30°	878.9	30.8
30°-40°	661.2	23.1
40°-50°	265.6	9.3
50°-60°	75.5	2.6
60°-70°	23.9	0.8
70°-80°	6.8	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1823.4	63.8
0°-40°	2484.6	87.0
0°-60°	2825.7	98.9
0°-90°	2857.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2857.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2833	
5°	2781	261
15°	2440	684
25°	1940	879
35°	1061	661
45°	328	266
55°	78	75
65°	22	24
75°	4	7
85°	0	1
90°	0	



TEST NUMBER: P858693

CATALOG NUMBER: LD4C35W2N2050D010 4LBMH_3000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	2832.9
2.5°	2815.6
5°	2781.1
7.5°	2716.4
10°	2634.5
12.5°	2535.4
15°	2440.5
17.5°	2332.7
20°	2216.2
22.5°	2091.3
25°	1940.4
27.5°	1759.2
30°	1548.0
32.5°	1310.8
35°	1060.8
37.5°	827.8
40°	621.0
42.5°	457.1
45°	327.6
47.5°	224.3
50°	155.3
52.5°	107.8
55°	77.6
57.5°	56.1
60°	43.1
62.5°	30.2
65°	21.6
67.5°	17.3
70°	12.9
72.5°	8.6
75°	4.3
77.5°	4.3
80°	4.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)