

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859064

Luminaire Tested: **LD4C55D010 EU4559027 4LBMLI**

Issue Date: 7/19/2024



Test Information

Test Method: LM-79-08
Report Number: P859064
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208178)
Test Lab: INNOVATION CENTER
Issue Date: 7/19/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C55D010 EU4559027 4LBMLI
Description: 4 INCH 5500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS
AND 4LBM TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5323.9 lumens
Efficiency: N/A
Efficacy: 83.3 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 63.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859064

CATALOG NUMBER: LD4C55D010 EU4559027 4LBMLI

Luminous Intensity Polar Plot





TEST NUMBER: P859064

CATALOG NUMBER: LD4C55D010 EU4559027 4LBMLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	64		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		67
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1031097
5°	1013590
10°	931311
15°	779925
20°	624849
25°	502064
30°	373742
35°	213506
40°	100202
45°	42549
50°	13551
55°	6897
60°	4742
65°	3750
70°	2299
75°	0
80°	0
85°	0



TEST NUMBER: P859064

CATALOG NUMBER: LD4C55D010 EU4559027 4LBMLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	759.9	14.3
10°-20°	1698.9	31.9
20°-30°	1689.1	31.7
30°-40°	919.8	17.3
40°-50°	212.6	4.0
50°-60°	29.9	0.6
60°-70°	11.1	0.2
70°-80°	2.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4148.0	77.9
0°-40°	5067.8	95.2
0°-60°	5310.3	99.7
0°-90°	5323.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5323.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8393	
5°	8219	760
15°	6132	1699
25°	3704	1689
35°	1424	920
45°	245	213
55°	32	30
65°	13	11
75°	0	3
85°	0	0
90°	0	



TEST NUMBER: P859064

CATALOG NUMBER: LD4C55D010 EU4559027 4LBMLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	8392.9
2.5°	8373.6
5°	8219.0
7.5°	7903.5
10°	7465.5
12.5°	6821.4
15°	6132.1
17.5°	5449.3
20°	4779.4
22.5°	4231.9
25°	3703.8
27.5°	3201.4
30°	2634.6
32.5°	2003.3
35°	1423.6
37.5°	959.6
40°	624.8
42.5°	392.8
45°	244.9
47.5°	141.8
50°	70.9
52.5°	38.7
55°	32.2
57.5°	19.3
60°	19.3
62.5°	12.9
65°	12.9
67.5°	6.4
70°	6.4
72.5°	6.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)