

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859129

Luminaire Tested: **LX4C55D010 EX4C559040 4LBMDH**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P859129
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-9)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C55D010 EX4C559040 4LBMDH
Description: 4 INCH 5500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 4000K, 90CRI LEDS
AND 4LRMD45 TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4260.0 lumens
Efficiency: N/A
Efficacy: 66.7 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.83
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 63.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859129

CATALOG NUMBER: LX4C55D010 EX4C559040 4LBMDH

Luminous Intensity Polar Plot





TEST NUMBER: P859129

CATALOG NUMBER: LX4C55D010 EX4C559040 4LBMDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	90	84	80	95	88	83	79	86	82	78		84	80	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	63	60	68	63	59		67	62	59		66
9	76	66	60	56	74	65	60	56	64	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	630496
5°	621978
10°	592806
15°	548546
20°	493797
25°	410240
30°	298216
35°	193305
40°	116977
45°	60288
50°	27293
55°	16428
60°	11032
65°	7878
70°	5927
75°	3940
80°	2476
85°	1692



TEST NUMBER: P859129

CATALOG NUMBER: LX4C55D010 EX4C559040 4LBMDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	472.2	11.1
10°-20°	1203.5	28.3
20°-30°	1360.9	31.9
30°-40°	822.5	19.3
40°-50°	288.1	6.8
50°-60°	73.7	1.7
60°-70°	28.2	0.7
70°-80°	9.5	0.2
80°-90°	1.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3036.6	71.3
0°-40°	3859.0	90.6
0°-60°	4220.8	99.1
0°-90°	4260.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4260.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5132	
5°	5044	472
15°	4313	1204
25°	3026	1361
35°	1289	822
45°	347	288
55°	77	74
65°	27	28
75°	8	9
85°	1	1
90°	0	



TEST NUMBER: P859129

CATALOG NUMBER: LX4C55D010 EX4C559040 4LBMDH

CANDELA DISTRIBUTION (FULL):

0°	
0°	5132.1
2.5°	5110.8
5°	5043.5
7.5°	4924.3
10°	4752.0
12.5°	4544.3
15°	4312.9
17.5°	4059.1
20°	3777.0
22.5°	3431.2
25°	3026.4
27.5°	2562.5
30°	2102.2
32.5°	1661.9
35°	1288.9
37.5°	977.3
40°	729.4
42.5°	524.1
45°	347.0
47.5°	213.6
50°	142.8
52.5°	102.7
55°	76.7
57.5°	59.0
60°	44.9
62.5°	35.4
65°	27.1
67.5°	21.2
70°	16.5
72.5°	11.8
75°	8.3
77.5°	5.9
80°	3.5
82.5°	2.4
85°	1.2
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)