

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859651

Luminaire Tested: **LX4C08D010 EX4C089030 4LBMDLI**

Issue Date: 2/18/2022



Test Information

Test Method: LM-79-08
Report Number: P859651
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2105-247-8)
Test Lab: INNOVATION CENTER
Issue Date: 2/18/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C08D010 EX4C089030 4LBMDLI
Description: 4 INCH 800 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS AND 4LRMD45 TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 727.0 lumens
Efficiency: N/A
Efficacy: 73.4 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.82
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859651

CATALOG NUMBER: LX4C08D010 EX4C089030 4LBMDLI

Luminous Intensity Polar Plot





TEST NUMBER: P859651

CATALOG NUMBER: LX4C08D010 EX4C089030 4LBMDLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	107	102	99	96	99	96	94		96	94	92		94
3	104	98	93	89	102	96	92	89	94	90	87		91	88	86		89
4	99	92	87	83	97	91	86	82	89	85	81		87	83	80		85
5	94	87	81	77	93	86	81	77	84	79	76		82	78	75		81
6	90	82	76	72	89	81	76	72	80	75	71		78	74	71		77
7	86	77	72	68	85	77	71	68	75	71	67		74	70	67		73
8	82	73	68	64	81	73	67	64	72	67	63		71	66	63		70
9	79	70	64	60	78	69	64	60	68	63	60		67	63	60		66
10	75	66	61	57	74	66	61	57	65	60	57		64	60	57		63

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	117313
5°	121300
10°	122528
15°	110386
20°	91726
25°	71966
30°	52672
35°	27221
40°	12926
45°	4552
50°	1032
55°	664
60°	467
65°	349
70°	251
75°	142
80°	141
85°	0



TEST NUMBER: P859651

CATALOG NUMBER: LX4C08D010 EX4C089030 4LBMDLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	93.9	12.9
10°-20°	239.0	32.9
20°-30°	241.9	33.3
30°-40°	123.3	17.0
40°-50°	24.2	3.3
50°-60°	2.9	0.4
60°-70°	1.2	0.2
70°-80°	0.4	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	574.9	79.1
0°-40°	698.2	96.0
0°-60°	725.3	99.8
0°-90°	727.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	727.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	955	
5°	984	94
15°	868	239
25°	531	242
35°	182	123
45°	26	24
55°	3	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P859651

CATALOG NUMBER: LX4C08D010 EX4C089030 4LBMDLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	954.9
2.5°	963.7
5°	983.6
7.5°	995.1
10°	982.2
12.5°	939.1
15°	867.9
17.5°	783.8
20°	701.6
22.5°	616.5
25°	530.9
27.5°	445.6
30°	371.3
32.5°	279.8
35°	181.5
37.5°	121.5
40°	80.6
42.5°	50.6
45°	26.2
47.5°	9.4
50°	5.4
52.5°	4.0
55°	3.1
57.5°	2.4
60°	1.9
62.5°	1.6
65°	1.2
67.5°	0.9
70°	0.7
72.5°	0.5
75°	0.3
77.5°	0.3
80°	0.2
82.5°	0.2
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)