

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859723

Luminaire Tested: **LX4C08D010 EX4C089050 4LBNH**

Issue Date: 2/8/2022



Test Information

Test Method: LM-79-08
Report Number: P859723
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C08D010 EX4C089050 4LBNH
Description: 4 INCH 800 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS AND 4LBN TRIM WITH H FINISH
Light Source: -
Ballast/Driver:

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 569.0 lumens
Efficiency: N/A
Efficacy: 57.5 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859723

CATALOG NUMBER: LX4C08D010 EX4C089050 4LBNH

Luminous Intensity Polar Plot





TEST NUMBER: P859723

CATALOG NUMBER: LX4C08D010 EX4C089050 4LBNH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	87767
5°	85808
10°	79340
15°	71199
20°	62676
25°	53937
30°	43437
35°	28915
40°	15043
45°	6811
50°	2962
55°	1992
60°	1278
65°	901
70°	754
75°	475
80°	0
85°	0



TEST NUMBER: P859723

CATALOG NUMBER: LX4C08D010 EX4C089050 4LBNH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	64.5	11.3
10°-20°	156.4	27.5
20°-30°	181.5	31.9
30°-40°	120.2	21.1
40°-50°	33.7	5.9
50°-60°	8.5	1.5
60°-70°	3.2	0.6
70°-80°	1.1	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	402.3	70.7
0°-40°	522.5	91.8
0°-60°	564.7	99.3
0°-90°	569.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	569.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	714	
5°	696	64
15°	560	156
25°	398	182
35°	193	120
45°	39	34
55°	9	8
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P859723

CATALOG NUMBER: LX4C08D010 EX4C089050 4LBNH

CANDELA DISTRIBUTION (FULL):

	0°
0°	714.4
2.5°	711.3
5°	695.8
7.5°	669.0
10°	636.0
12.5°	598.9
15°	559.8
17.5°	521.6
20°	479.4
22.5°	440.2
25°	397.9
27.5°	357.7
30°	306.2
32.5°	251.5
35°	192.8
37.5°	138.1
40°	93.8
42.5°	60.8
45°	39.2
47.5°	23.7
50°	15.5
52.5°	11.3
55°	9.3
57.5°	7.2
60°	5.2
62.5°	4.1
65°	3.1
67.5°	2.1
70°	2.1
72.5°	1.0
75°	1.0
77.5°	1.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)