

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P859771

Luminaire Tested: **LX4C08D010 EX4C089835 4LBSLI**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P859771
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P208407)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX4C08D010 EX4C089835 4LBSLI
Description:
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 814.1 lumens
Efficiency: N/A
Efficacy: 82.2 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P859771

CATALOG NUMBER: LX4C08D010 EX4C089835 4LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P859771

CATALOG NUMBER: LX4C08D010 EX4C089835 4LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	98		98	96	95		95
2	104	98	93	88	102	96	91	87	93	89	85		90	86	84		87
3	97	89	82	77	95	87	81	77	84	79	75		82	78	74		79
4	90	81	73	68	88	79	73	68	77	71	67		75	70	66		73
5	84	73	66	61	82	72	65	60	70	64	60		69	63	59		67
6	79	67	60	54	77	66	59	54	65	58	54		63	58	53		62
7	74	62	54	49	72	61	54	49	60	53	49		58	53	48		57
8	69	57	50	45	68	57	50	45	55	49	45		54	49	44		53
9	65	53	46	41	64	53	46	41	52	45	41		51	45	41		50
10	61	50	43	38	60	49	42	38	48	42	38		47	42	38		46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	71415
5°	69801
10°	65543
15°	60986
20°	56557
25°	51551
30°	45906
35°	40689
40°	36565
45°	32715
50°	28076
55°	22597
60°	16831
65°	10727
70°	5172
75°	854
80°	637
85°	0



TEST NUMBER: P859771

CATALOG NUMBER: LX4C08D010 EX4C089835 4LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.7	6.5
10°-20°	134.4	16.5
20°-30°	174.2	21.4
30°-40°	170.7	21.0
40°-50°	144.7	17.8
50°-60°	94.8	11.7
60°-70°	38.1	4.7
70°-80°	4.4	0.5
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	361.3	44.4
0°-40°	532.0	65.4
0°-60°	771.5	94.8
0°-90°	814.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	814.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	581	
5°	566	53
15°	480	134
25°	380	174
35°	271	171
45°	188	145
55°	106	95
65°	37	38
75°	2	4
85°	0	0
90°	0	



TEST NUMBER: P859771

CATALOG NUMBER: LX4C08D010 EX4C089835 4LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	581.3
2.5°	576.9
5°	566.0
7.5°	548.0
10°	525.4
12.5°	501.2
15°	479.5
17.5°	456.0
20°	432.6
22.5°	407.4
25°	380.3
27.5°	352.4
30°	323.6
32.5°	296.5
35°	271.3
37.5°	250.6
40°	228.0
42.5°	208.2
45°	188.3
47.5°	167.6
50°	146.9
52.5°	126.2
55°	105.5
57.5°	86.5
60°	68.5
62.5°	52.3
65°	36.9
67.5°	24.3
70°	14.4
72.5°	6.3
75°	1.8
77.5°	0.9
80°	0.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)