

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P#

Luminaire Tested: **LD4C70D010 EX4C709035 4LBSQH**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P#
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C70D010 EX4C709035 4LBSQH
Description: 4 INCH 7000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3500K, 90CRI LEDS
AND 4LBSQ TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5658.0 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 78
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709035 4LBSQH

Luminous Intensity Polar Plot





TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709035 4LBSQH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	541332
5°	533462
10°	511177
15°	482811
20°	450668
25°	409108
30°	341567
35°	247444
40°	154902
45°	88546
50°	46159
55°	25873
60°	16480
65°	9749
70°	7222
75°	3169
80°	4723
85°	0



TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709035 4LBSQH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	516.2	9.1
10°-20°	1354.3	23.9
20°-30°	1740.5	30.8
30°-40°	1309.5	23.1
40°-50°	525.9	9.3
50°-60°	149.5	2.6
60°-70°	47.3	0.8
70°-80°	13.5	0.2
80°-90°	1.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3611.1	63.8
0°-40°	4920.6	87.0
0°-60°	5596.0	98.9
0°-90°	5658.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5658.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5610	
5°	5508	516
15°	4833	1354
25°	3843	1741
35°	2101	1310
45°	649	526
55°	154	150
65°	43	47
75°	8	13
85°	0	1
90°	0	



TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709035 4LBSQH

CANDELA DISTRIBUTION (FULL):

0°	
0°	5610.3
2.5°	5576.1
5°	5507.7
7.5°	5379.6
10°	5217.3
12.5°	5021.2
15°	4833.3
17.5°	4619.7
20°	4389.0
22.5°	4141.7
25°	3842.7
27.5°	3483.9
30°	3065.7
32.5°	2595.8
35°	2100.7
37.5°	1639.4
40°	1229.8
42.5°	905.1
45°	648.9
47.5°	444.2
50°	307.5
52.5°	213.6
55°	153.8
57.5°	111.1
60°	85.4
62.5°	59.8
65°	42.7
67.5°	34.2
70°	25.6
72.5°	17.1
75°	8.5
77.5°	8.5
80°	8.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)