

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P#

Luminaire Tested: **LD4C70D010 EX4C709050 4LBSQH**

Issue Date: 2/9/2022



Test Information

Test Method: LM-79-08
Report Number: P#
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/9/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD4C70D010 EX4C709050 4LBSQH
Description: 4 INCH 7000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 5000K, 90CRI LEDS
AND 4LBSQ TRIM WITH H FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5782.0 lumens
Efficiency: N/A
Efficacy: 74.1 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Rectangular (W 0.33' x L: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 78
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709050 4LBSQH

Luminous Intensity Polar Plot





TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709050 4LBSQH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	553190
5°	545162
10°	522376
15°	493390
20°	460546
25°	418072
30°	349054
35°	252874
40°	158291
45°	90484
50°	47180
55°	26428
60°	16847
65°	9954
70°	7391
75°	3243
80°	4834
85°	0



TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709050 4LBSQH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	527.5	9.1
10°-20°	1384.0	23.9
20°-30°	1778.6	30.8
30°-40°	1338.2	23.1
40°-50°	537.5	9.3
50°-60°	152.8	2.6
60°-70°	48.4	0.8
70°-80°	13.8	0.2
80°-90°	1.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3690.2	63.8
0°-40°	5028.4	87.0
0°-60°	5718.7	98.9
0°-90°	5782.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5782.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5733	
5°	5628	528
15°	4939	1384
25°	3927	1779
35°	2147	1338
45°	663	537
55°	157	153
65°	44	48
75°	9	14
85°	0	1
90°	0	



TEST NUMBER: P#

CATALOG NUMBER: LD4C70D010 EX4C709050 4LBSQH

CANDELA DISTRIBUTION (FULL):

	0°
0°	5733.2
2.5°	5698.3
5°	5628.5
7.5°	5497.5
10°	5331.6
12.5°	5131.2
15°	4939.2
17.5°	4720.9
20°	4485.2
22.5°	4232.4
25°	3926.9
27.5°	3560.2
30°	3132.9
32.5°	2652.7
35°	2146.8
37.5°	1675.4
40°	1256.7
42.5°	925.0
45°	663.1
47.5°	454.0
50°	314.3
52.5°	218.2
55°	157.1
57.5°	113.5
60°	87.3
62.5°	61.1
65°	43.6
67.5°	34.9
70°	26.2
72.5°	17.5
75°	8.7
77.5°	8.7
80°	8.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)