

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P778614

Luminaire Tested: LER4D02D010-EC4DR300210IC9024-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P778614
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D02D010-EC4DR300210IC9024-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 328.2 lumens
Efficiency: N/A
Efficacy: 64.3 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P778614

CATALOG NUMBER: LER4D02D010-EC4DR300210IC9024-4LBS1LI

Luminous Intensity Polar Plot



TEST NUMBER: P778614

CATALOG NUMBER: LER4D02D010-EC4DR300210IC9024-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	113	111	109	112	110	109	107		106	105	104		103	102	101		99	99	98
2	111	107	104	101	109	105	102	100		102	100	98		99	97	96		97	95	94
3	107	102	98	95	105	101	97	94		98	95	93		96	93	91		94	92	90
4	103	98	93	90	102	96	93	90		94	91	89		93	90	88		91	89	87
5	100	94	89	86	98	93	89	86		91	88	85		90	86	84		88	86	83
6	97	90	85	82	95	89	85	82		88	84	81		87	83	81		85	83	80
7	94	87	82	79	92	86	82	79		85	81	78		84	81	78		83	80	78
8	91	84	79	76	90	83	79	76		82	78	76		81	78	75		80	77	75
9	88	81	76	73	87	80	76	73		80	76	73		79	75	73		78	75	73
10	85	78	74	71	85	78	74	71		77	73	71		76	73	71		76	73	70

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	80769	80769	80769
5°	78457	78365	78457
10°	67954	67472	67931
15°	44337	44091	43877
20°	22050	22873	22017
25°	11106	12525	10878
30°	4446	4843	3871
35°	2065	1972	1654
40°	889	989	839
45°	628	779	628
50°	214	572	226
55°	120	240	133
60°	92	107	92
65°	54	54	54
70°	45	22	45
75°	0	30	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°

Vertical Angle: 45°

Luminance: 779 cd/sqm



TEST NUMBER: P778614

CATALOG NUMBER: LER4D02D010-EC4DR300210IC9024-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	92.8	28.3
10°-20°	149.4	45.5
20°-30°	64.6	19.7
30°-40°	14.7	4.5
40°-50°	5.1	1.5
50°-60°	1.2	0.4
60°-70°	0.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	306.8	93.5
0°-40°	321.5	98.0
0°-60°	327.8	99.9
0°-90°	328.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	328.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1055	1055	1055	1055	1055	
5°	1021	1020	1020	1022	1021	93
15°	560	553	556	555	554	150
25°	132	136	148	133	129	63
35°	22	22	21	21	18	15
45°	6	7	7	7	6	4
55°	1	1	2	1	1	1
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	



TEST NUMBER: P778614

CATALOG NUMBER: LER4D02D010-EC4DR300210IC9024-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1055.2	1055.2	1055.2	1055.2	1055.2
2.5°	1048.2	1047.5	1047.9	1048.4	1048.7
5°	1021.1	1020.1	1019.9	1022.0	1021.1
7.5°	966.2	964.8	962.7	967.5	972.0
10°	874.3	872.7	868.1	870.4	874.0
12.5°	738.6	733.5	733.4	740.7	739.7
15°	559.5	552.7	556.4	554.7	553.7
17.5°	376.3	373.6	378.6	377.1	370.6
20°	270.7	271.3	280.8	276.0	270.3
22.5°	197.5	199.9	211.2	198.9	194.4
25°	131.5	136.5	148.3	133.0	128.8
27.5°	80.9	83.1	95.1	79.8	77.6
30°	50.3	49.2	54.8	47.0	43.8
32.5°	33.0	31.6	33.3	30.0	27.3
35°	22.1	22.5	21.1	21.0	17.7
37.5°	13.8	15.9	14.0	14.9	11.4
40°	8.9	11.5	9.9	10.9	8.4
42.5°	7.3	8.9	8.1	8.7	7.4
45°	5.8	7.2	7.2	7.2	5.8
47.5°	3.2	4.8	6.2	4.9	3.4
50°	1.8	2.4	4.8	2.5	1.9
52.5°	1.3	1.4	3.3	1.4	1.3
55°	0.9	1.0	1.8	1.0	1.0
57.5°	0.7	0.8	0.9	0.8	0.7
60°	0.6	0.6	0.7	0.6	0.6
62.5°	0.4	0.4	0.5	0.4	0.4
65°	0.3	0.3	0.3	0.3	0.3
67.5°	0.2	0.2	0.2	0.2	0.2
70°	0.2	0.1	0.1	0.1	0.2
72.5°	0.1	0.1	0.1	0.1	0.1
75°	0.0	0.0	0.1	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180° - - 45°-225° - - - 90°-270°







(END OF REPORT)