

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P778796

Luminaire Tested: LER4D02D010-EC4DR650210IC9040-4LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P778796
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D02D010-EC4DR650210IC9040-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 323.8 lumens
Efficiency: N/A
Efficacy: 63.5 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P778796

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1B

Luminous Intensity Polar Plot



CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1B

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100			
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93	93	93	93			
2	107	102	97	94	105	100	96	92	97	93	90	94	91	89	91	89	87	85	85	85	85			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78	78	78	78			
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72	72	72	72			
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66	66	66	66			
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61	61	61	61			
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56	56	56	56			
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52	52	52	52			
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49	49	49	49			
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46	46	46	46			

	0°
0°	17171
5°	17125
10°	17109
15°	16585
20°	15097
25°	13159
30°	10945
35°	8670
40°	6259
45°	3948
50°	2063
55°	1100
60°	572
65°	318
70°	137
75°	135
80°	101
85°	67

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3948 cd/sqm



TEST NUMBER: P778796

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	27.8	8.6
10°-20°	76.1	23.5
20°-30°	93.1	28.7
30°-40°	75.5	23.3
40°-50°	37.6	11.6
50°-60°	10.5	3.2
60°-70°	2.4	0.7
70°-80°	0.6	0.2
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	197.0	60.8
0°-40°	272.5	84.2
0°-60°	320.6	99.0
0°-90°	323.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	323.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	294	
5°	292	28
15°	274	76
25°	204	93
35°	122	76
45°	48	38
55°	11	11
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P778796

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	294.0
2.5°	293.8
5°	292.1
7.5°	291.2
10°	288.5
12.5°	283.2
15°	274.3
17.5°	260.4
20°	242.9
22.5°	224.1
25°	204.2
27.5°	182.9
30°	162.3
32.5°	141.9
35°	121.6
37.5°	101.4
40°	82.1
42.5°	64.0
45°	47.8
47.5°	33.3
50°	22.7
52.5°	15.6
55°	10.8
57.5°	7.3
60°	4.9
62.5°	3.4
65°	2.3
67.5°	1.1
70°	0.8
72.5°	0.7
75°	0.6
77.5°	0.5
80°	0.3
82.5°	0.2
85°	0.1
87.5°	0.1
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)