

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P778797

Luminaire Tested: LER4D02D010-EC4DR650210IC9040-4LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P778797
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D02D010-EC4DR650210IC9040-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 348.8 lumens
Efficiency: N/A
Efficacy: 68.4 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P778797

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P778797

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	107	105		111	108	105	103		104	102	100		100	99	97		97	95	94
2	107	102	97	94		105	100	96	92		97	93	90		94	91	88		91	89	87
3	101	94	88	84		99	92	87	83		90	86	82		87	84	81		85	82	80
4	95	87	81	76		93	86	80	76		84	79	75		82	77	74		80	76	73
5	90	81	74	70		88	80	74	69		78	73	69		76	72	68		75	71	68
6	85	75	69	64		83	74	68	64		73	67	63		71	67	63		70	66	62
7	80	70	64	59		79	69	63	59		68	63	59		67	62	58		66	61	58
8	76	66	59	55		75	65	59	55		64	58	54		63	58	54		62	57	54
9	72	61	55	51		71	61	55	51		60	54	51		59	54	50		58	54	50
10	68	58	52	47		67	57	51	47		57	51	47		56	51	47		55	50	47

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	18497
5°	18450
10°	18432
15°	17861
20°	16265
25°	14171
30°	11782
35°	9340
40°	6740
45°	4262
50°	2217
55°	1181
60°	619
65°	345
70°	154
75°	158
80°	101
85°	67

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4262 cd/sqm



TEST NUMBER: P778797

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.9	8.6
10°-20°	82.0	23.5
20°-30°	100.2	28.7
30°-40°	81.3	23.3
40°-50°	40.5	11.6
50°-60°	11.3	3.2
60°-70°	2.6	0.7
70°-80°	0.7	0.2
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	212.2	60.8
0°-40°	293.5	84.2
0°-60°	345.3	99.0
0°-90°	348.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	348.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	317	
5°	315	30
15°	295	82
25°	220	100
35°	131	81
45°	52	41
55°	12	11
65°	2	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P778797

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9040-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	316.7
2.5°	316.4
5°	314.7
7.5°	313.6
10°	310.8
12.5°	305.0
15°	295.4
17.5°	280.5
20°	261.7
22.5°	241.4
25°	219.9
27.5°	197.0
30°	174.7
32.5°	152.9
35°	131.0
37.5°	109.1
40°	88.4
42.5°	69.0
45°	51.6
47.5°	35.9
50°	24.4
52.5°	16.8
55°	11.6
57.5°	7.8
60°	5.3
62.5°	3.7
65°	2.5
67.5°	1.3
70°	0.9
72.5°	0.8
75°	0.7
77.5°	0.5
80°	0.3
82.5°	0.2
85°	0.1
87.5°	0.1
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)