

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P778802

Luminaire Tested: LER4D02D010-EC4DR650210IC9050-4LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P778802
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D02D010-EC4DR650210IC9050-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 361.8 lumens
Efficiency: N/A
Efficacy: 70.9 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P778802

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9050-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P778802

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9050-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	19186
5°	19142
10°	19126
15°	18532
20°	16874
25°	14699
30°	12227
35°	9689
40°	6991
45°	4419
50°	2299
55°	1222
60°	642
65°	359
70°	154
75°	158
80°	101
85°	134

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4419 cd/sqm



TEST NUMBER: P778802

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9050-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.1	8.6
10°-20°	85.1	23.5
20°-30°	104.0	28.7
30°-40°	84.4	23.3
40°-50°	42.1	11.6
50°-60°	11.7	3.2
60°-70°	2.7	0.7
70°-80°	0.7	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	220.1	60.8
0°-40°	304.5	84.2
0°-60°	358.3	99.0
0°-90°	361.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	361.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	328	
5°	326	31
15°	306	85
25°	228	104
35°	136	84
45°	54	42
55°	12	12
65°	3	3
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P778802

CATALOG NUMBER: LER4D02D010-EC4DR650210IC9050-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	328.5
2.5°	328.3
5°	326.5
7.5°	325.4
10°	322.5
12.5°	316.5
15°	306.5
17.5°	291.0
20°	271.5
22.5°	250.4
25°	228.1
27.5°	204.4
30°	181.3
32.5°	158.6
35°	135.9
37.5°	113.3
40°	91.7
42.5°	71.6
45°	53.5
47.5°	37.3
50°	25.3
52.5°	17.5
55°	12.0
57.5°	8.1
60°	5.5
62.5°	3.8
65°	2.6
67.5°	1.3
70°	0.9
72.5°	0.8
75°	0.7
77.5°	0.5
80°	0.3
82.5°	0.2
85°	0.2
87.5°	0.1
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°







(END OF REPORT)