

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779095

Luminaire Tested: LER4D05D010-EC4DR650210IC9024-4LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779095
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D05D010-EC4DR650210IC9024-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 485.9 lumens
Efficiency: N/A
Efficacy: 64.8 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779095

CATALOG NUMBER: LER4D05D010-EC4DR650210IC9024-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P779095

CATALOG NUMBER: LER4D05D010-EC4DR650210IC9024-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93			
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78			
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72			
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66			
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61			
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49			
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	25768
5°	25702
10°	25679
15°	24887
20°	22654
25°	19745
30°	16421
35°	13012
40°	9393
45°	5930
50°	3089
55°	1650
60°	864
65°	470
70°	188
75°	226
80°	168
85°	134

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5930 cd/sqm



TEST NUMBER: P779095

CATALOG NUMBER: LER4D05D010-EC4DR650210IC9024-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	41.7	8.6
10°-20°	114.2	23.5
20°-30°	139.6	28.7
30°-40°	113.3	23.3
40°-50°	56.4	11.6
50°-60°	15.8	3.2
60°-70°	3.6	0.7
70°-80°	0.9	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	295.6	60.8
0°-40°	408.9	84.2
0°-60°	481.1	99.0
0°-90°	485.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	485.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	441	
5°	438	42
15°	412	114
25°	306	140
35°	182	113
45°	72	56
55°	16	16
65°	3	4
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P779095

CATALOG NUMBER: LER4D05D010-EC4DR650210IC9024-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	441.2
2.5°	440.8
5°	438.4
7.5°	436.9
10°	433.0
12.5°	425.0
15°	411.6
17.5°	390.7
20°	364.5
22.5°	336.3
25°	306.4
27.5°	274.4
30°	243.5
32.5°	213.0
35°	182.5
37.5°	152.1
40°	123.2
42.5°	96.1
45°	71.8
47.5°	50.0
50°	34.0
52.5°	23.5
55°	16.2
57.5°	10.9
60°	7.4
62.5°	5.1
65°	3.4
67.5°	1.8
70°	1.1
72.5°	1.1
75°	1.0
77.5°	0.6
80°	0.5
82.5°	0.3
85°	0.2
87.5°	0.1
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)