

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779409

Luminaire Tested: LER4D08D010-EC4DR650210IC9027-4LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779409
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D08D010-EC4DR650210IC9027-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 667.8 lumens
Efficiency: N/A
Efficacy: 75.0 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 8.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779409

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9027-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P779409

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9027-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100				
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	97	95	94	93	93				
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85	85	85				
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78	78	78				
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72	72	72				
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66	66	66				
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61	61	61				
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56	56	56				
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52	52	52				
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49	49	49				
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46	46	46				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	35410
5°	35323
10°	35292
15°	34205
20°	31138
25°	27136
30°	22572
35°	17882
40°	12908
45°	8152
50°	4252
55°	2260
60°	1180
65°	650
70°	273
75°	293
80°	202
85°	201

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8152 cd/sqm



TEST NUMBER: P779409

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9027-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.3	8.6
10°-20°	157.0	23.5
20°-30°	191.9	28.7
30°-40°	155.7	23.3
40°-50°	77.6	11.6
50°-60°	21.7	3.2
60°-70°	4.9	0.7
70°-80°	1.3	0.2
80°-90°	0.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	406.3	60.8
0°-40°	562.0	84.2
0°-60°	661.3	99.0
0°-90°	667.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	667.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	606	
5°	602	57
15°	566	157
25°	421	192
35°	251	156
45°	99	78
55°	22	22
65°	5	5
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P779409

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9027-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	606.3
2.5°	605.8
5°	602.5
7.5°	600.5
10°	595.1
12.5°	584.0
15°	565.7
17.5°	537.0
20°	501.0
22.5°	462.1
25°	421.1
27.5°	377.2
30°	334.7
32.5°	292.7
35°	250.8
37.5°	209.0
40°	169.3
42.5°	132.1
45°	98.7
47.5°	68.8
50°	46.8
52.5°	32.3
55°	22.2
57.5°	15.0
60°	10.1
62.5°	7.0
65°	4.7
67.5°	2.4
70°	1.6
72.5°	1.5
75°	1.3
77.5°	0.9
80°	0.6
82.5°	0.5
85°	0.3
87.5°	0.2
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)