

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779425

Luminaire Tested: LER4D08D010-EC4DR650210IC9050-4LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779425
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D08D010-EC4DR650210IC9050-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 739.2 lumens
Efficiency: N/A
Efficacy: 83.1 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 8.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779425

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9050-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P779425

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9050-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93						
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85						
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78						
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72						
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66						
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61						
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56						
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52						
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49						
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46						

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39201
5°	39098
10°	39064
15°	37863
20°	34470
25°	30036
30°	24986
35°	19799
40°	14288
45°	9028
50°	4707
55°	2505
60°	1308
65°	719
70°	307
75°	338
80°	235
85°	201

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9028 cd/sqm



TEST NUMBER: P779425

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9050-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	63.5	8.6
10°-20°	173.8	23.5
20°-30°	212.5	28.7
30°-40°	172.4	23.3
40°-50°	85.9	11.6
50°-60°	24.0	3.2
60°-70°	5.4	0.7
70°-80°	1.4	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	449.7	60.8
0°-40°	622.1	84.2
0°-60°	732.0	99.0
0°-90°	739.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	739.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	671	
5°	667	63
15°	626	174
25°	466	212
35°	278	172
45°	109	86
55°	25	24
65°	5	5
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P779425

CATALOG NUMBER: LER4D08D010-EC4DR650210IC9050-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	671.2
2.5°	670.7
5°	666.9
7.5°	664.7
10°	658.7
12.5°	646.5
15°	626.2
17.5°	594.4
20°	554.6
22.5°	511.6
25°	466.1
27.5°	417.5
30°	370.5
32.5°	324.0
35°	277.7
37.5°	231.4
40°	187.4
42.5°	146.2
45°	109.3
47.5°	76.1
50°	51.8
52.5°	35.7
55°	24.6
57.5°	16.6
60°	11.2
62.5°	7.8
65°	5.2
67.5°	2.6
70°	1.8
72.5°	1.7
75°	1.5
77.5°	1.0
80°	0.7
82.5°	0.5
85°	0.3
87.5°	0.2
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)