

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779690

Luminaire Tested: LER4D10D010-EC4DR550210IC9050-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P779690
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D10D010-EC4DR550210IC9050-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1210.9 lumens
Efficiency: N/A
Efficacy: 103.5 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779690

CATALOG NUMBER: LER4D10D010-EC4DR550210IC9050-4LBS1LI

Luminous Intensity Polar Plot



TEST NUMBER: P779690

CATALOG NUMBER: LER4D10D010-EC4DR550210IC9050-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82
4	97	90	84	80	95	88	83	79	86	82	78	84	81	78	82	79	77
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71
6	88	79	73	68	86	78	72	68	76	71	68	75	70	67	74	70	67
7	83	74	68	64	82	73	67	63	72	67	63	71	66	63	70	65	62
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	62	58
9	75	66	60	56	74	65	59	55	64	59	55	63	58	55	62	58	55
10	72	62	56	52	71	61	56	52	61	56	52	60	55	52	59	55	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	148354
5°	142461
10°	141922
15°	137853
20°	123610
25°	102147
30°	77162
35°	55954
40°	35800
45°	16348
50°	5354
55°	2305
60°	983
65°	129
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 16348 cd/sqm



TEST NUMBER: P779690

CATALOG NUMBER: LER4D10D010-EC4DR550210IC9050-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	123.6	10.2
10°-20°	337.3	27.9
20°-30°	384.4	31.7
30°-40°	261.7	21.6
40°-50°	90.2	7.4
50°-60°	12.5	1.0
60°-70°	1.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	845.3	69.8
0°-40°	1107.0	91.4
0°-60°	1209.7	99.9
0°-90°	1210.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1210.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1358	
5°	1299	124
15°	1219	337
25°	847	384
35°	420	262
45°	106	90
55°	12	12
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P779690

CATALOG NUMBER: LER4D10D010-EC4DR550210IC9050-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1357.8
2.5°	1326.7
5°	1298.9
7.5°	1285.3
10°	1279.2
12.5°	1259.1
15°	1218.7
17.5°	1154.6
20°	1063.1
22.5°	957.3
25°	847.3
27.5°	732.7
30°	611.6
32.5°	509.0
35°	419.5
37.5°	334.3
40°	251.0
42.5°	173.9
45°	105.8
47.5°	57.1
50°	31.5
52.5°	18.7
55°	12.1
57.5°	7.7
60°	4.5
62.5°	2.0
65°	0.5
67.5°	0.2
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)