

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779696

Luminaire Tested: LER4D10D010-EC4DR600210IC9027-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P779696
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D10D010-EC4DR600210IC9027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 957.4 lumens
Efficiency: N/A
Efficacy: 81.8 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779696

CATALOG NUMBER: LER4D10D010-EC4DR600210IC9027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P779696

CATALOG NUMBER: LER4D10D010-EC4DR600210IC9027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82
4	97	90	84	80	95	88	83	79	86	82	78	84	81	78	82	79	77
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71
6	87	79	73	68	86	78	72	68	76	71	68	75	70	67	74	70	67
7	83	74	68	63	82	73	67	63	72	67	63	71	66	63	69	65	62
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	61	58
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55
10	72	62	56	52	71	61	56	52	61	55	52	60	55	52	59	55	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	104683
5°	104425
10°	107895
15°	108002
20°	99378
25°	84522
30°	64406
35°	45550
40°	26743
45°	10785
50°	3604
55°	1733
60°	721
65°	103
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10785 cd/sqm



TEST NUMBER: P779696

CATALOG NUMBER: LER4D10D010-EC4DR600210IC9027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	91.8	9.6
10°-20°	264.5	27.6
20°-30°	316.6	33.1
30°-40°	211.8	22.1
40°-50°	62.8	6.6
50°-60°	9.0	0.9
60°-70°	0.9	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	673.0	70.3
0°-40°	884.7	92.4
0°-60°	956.5	99.9
0°-90°	957.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	957.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	958	
5°	952	92
15°	955	265
25°	701	317
35°	342	212
45°	70	63
55°	9	9
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P779696

CATALOG NUMBER: LER4D10D010-EC4DR600210IC9027-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	958.1
2.5°	956.8
5°	952.1
7.5°	965.0
10°	972.5
12.5°	971.1
15°	954.8
17.5°	916.4
20°	854.7
22.5°	780.6
25°	701.1
27.5°	611.6
30°	510.5
32.5°	420.3
35°	341.5
37.5°	262.5
40°	187.5
42.5°	123.6
45°	69.8
47.5°	35.8
50°	21.2
52.5°	13.8
55°	9.1
57.5°	5.8
60°	3.3
62.5°	1.4
65°	0.4
67.5°	0.1
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)