

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779716

Luminaire Tested: LER4D10D010-EC4DR650210IC9024-4LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779716
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D10D010-EC4DR650210IC9024-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 746.6 lumens
Efficiency: N/A
Efficacy: 63.8 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779716

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P779716

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	39598
5°	39497
10°	39461
15°	38244
20°	34818
25°	30346
30°	25236
35°	19999
40°	14432
45°	9119
50°	4752
55°	2525
60°	1320
65°	732
70°	307
75°	338
80°	235
85°	201

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9119 cd/sqm



TEST NUMBER: P779716

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	64.1	8.6
10°-20°	175.6	23.5
20°-30°	214.6	28.7
30°-40°	174.1	23.3
40°-50°	86.8	11.6
50°-60°	24.2	3.2
60°-70°	5.5	0.7
70°-80°	1.4	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	454.3	60.8
0°-40°	628.4	84.2
0°-60°	739.3	99.0
0°-90°	746.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	746.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	678	
5°	674	64
15°	632	176
25°	471	215
35°	280	174
45°	110	87
55°	25	24
65°	5	5
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P779716

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	678.0
2.5°	677.5
5°	673.7
7.5°	671.5
10°	665.4
12.5°	653.0
15°	632.5
17.5°	600.5
20°	560.2
22.5°	516.7
25°	470.9
27.5°	421.7
30°	374.2
32.5°	327.3
35°	280.5
37.5°	233.7
40°	189.3
42.5°	147.6
45°	110.4
47.5°	76.9
50°	52.3
52.5°	36.0
55°	24.8
57.5°	16.7
60°	11.3
62.5°	7.8
65°	5.3
67.5°	2.7
70°	1.8
72.5°	1.7
75°	1.5
77.5°	1.0
80°	0.7
82.5°	0.5
85°	0.3
87.5°	0.2
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)