

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779718

Luminaire Tested: LER4D10D010-EC4DR650210IC9024-4LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779718
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D10D010-EC4DR650210IC9024-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 844.4 lumens
Efficiency: N/A
Efficacy: 72.2 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779718

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P779718

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	44778
5°	44668
10°	44627
15°	43250
20°	39373
25°	34309
30°	28540
35°	22609
40°	16323
45°	10308
50°	5370
55°	2861
60°	1495
65°	829
70°	342
75°	384
80°	269
85°	201

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10308 cd/sqm



TEST NUMBER: P779718

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.5	8.6
10°-20°	198.5	23.5
20°-30°	242.7	28.7
30°-40°	196.9	23.3
40°-50°	98.1	11.6
50°-60°	27.4	3.2
60°-70°	6.2	0.7
70°-80°	1.6	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	513.7	60.8
0°-40°	710.6	84.2
0°-60°	836.1	99.0
0°-90°	844.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	844.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	767	
5°	762	73
15°	715	199
25°	532	243
35°	317	197
45°	125	98
55°	28	27
65°	6	6
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P779718

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9024-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	766.7
2.5°	766.1
5°	761.9
7.5°	759.4
10°	752.5
12.5°	738.5
15°	715.3
17.5°	679.1
20°	633.5
22.5°	584.4
25°	532.4
27.5°	476.9
30°	423.2
32.5°	370.1
35°	317.1
37.5°	264.3
40°	214.1
42.5°	167.0
45°	124.8
47.5°	87.0
50°	59.1
52.5°	40.8
55°	28.1
57.5°	18.9
60°	12.8
62.5°	8.9
65°	6.0
67.5°	3.0
70°	2.0
72.5°	1.9
75°	1.7
77.5°	1.1
80°	0.8
82.5°	0.6
85°	0.3
87.5°	0.2
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°







(END OF REPORT)