

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P779723

Luminaire Tested: LER4D10D010-EC4DR650210IC9027-4LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P779723
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D10D010-EC4DR650210IC9027-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 848.2 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P779723

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9027-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P779723

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9027-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	44983
5°	44867
10°	44834
15°	43450
20°	39554
25°	34470
30°	28668
35°	22716
40°	16392
45°	10357
50°	5397
55°	2871
60°	1507
65°	829
70°	359
75°	384
80°	269
85°	201

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10357 cd/sqm



TEST NUMBER: P779723

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9027-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.8	8.6
10°-20°	199.5	23.5
20°-30°	243.8	28.7
30°-40°	197.8	23.3
40°-50°	98.6	11.6
50°-60°	27.5	3.2
60°-70°	6.2	0.7
70°-80°	1.6	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	516.1	60.8
0°-40°	713.9	84.2
0°-60°	840.0	99.0
0°-90°	848.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	848.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	770	
5°	765	73
15°	719	199
25°	535	244
35°	319	198
45°	125	99
55°	28	27
65°	6	6
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P779723

CATALOG NUMBER: LER4D10D010-EC4DR650210IC9027-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	770.2
2.5°	769.6
5°	765.3
7.5°	762.8
10°	756.0
12.5°	741.9
15°	718.6
17.5°	682.2
20°	636.4
22.5°	587.1
25°	534.9
27.5°	479.1
30°	425.1
32.5°	371.8
35°	318.6
37.5°	265.5
40°	215.0
42.5°	167.8
45°	125.4
47.5°	87.4
50°	59.4
52.5°	41.0
55°	28.2
57.5°	19.0
60°	12.9
62.5°	8.9
65°	6.0
67.5°	3.0
70°	2.1
72.5°	1.9
75°	1.7
77.5°	1.1
80°	0.8
82.5°	0.6
85°	0.3
87.5°	0.2
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)